QUICK REFERENCE GUIDE > RGV3-488L

Gas Range, 48", 8 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- · Made from quality materials and real stainless steel

DIMENSIONS

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Burner ratings	
Maximum burner power	17000 BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power centre	15000BTU
Power front centre (2)	15000BTU
Power front left	17000BTU
Power front right	17000BTU
Total cooktop power	116000 BTU

Capacity

Shelf positions	5
Total capacity (main oven)	5.3 cu ft
Total capacity second oven	2.4 cu ft
Usable capacity (main oven)	3.9 cu ft

Cleaning

Easy clean porcelain basepan

Controls

Electric circuit 3 wire

QUICK REFERENCE GUIDE > RGV3-488L Date: 05.07.2024 > 2

Metal illuminated dials		Oven functions		Safety	
		Bake	•	ADA compliant	•
Con Boundary and		Broil	•	Full extension telescopic sliding shelves	•
Gas Requirements		Convection bake	•		
Fitting and pipe	½ NPT, min. 5/8" ∑ flex line	Slow cook	•		
Supply Pressure (LPG)	11" to 14" W.C			Secondary oven features	
				3/4 Extension racks	2
		Power Requirements		Electronic oven control	•
Main oven features		Service	15 A	Internal light	•
Broil pan	•	Supply	120 V, 60 Hz		
Electronic oven control	•			Secondary oven functions	
Full extension telescopic racks	•	Product Dimensions		Bake	
Internal light	•	Depth	29 1/8 "	Convection bake	•
		Depth (excluding handles)	29 1/8 "	Number of secondary oven functions	4
Main oven functions		Height	35 3/4 - 36 3/4 "	Proof	•
		Width	47 7/8 "	Slow cook	•
Bake	•				
Broil Convertion hale	•				
Convection bake	•	Rangetop features		0.00	0400=
Number of oven functions	4	Sealed range top	•	SKU	81995
Slow cook	•	Vent trim included	•		
				The product dimensions and specifications in this page apply to t	the specific
Oven features				product and model. Under our policy of continuous improvement dimensions and specifications may change at any time. You shou	
Auto re-ignition system	•	Recommended Back Guards Ventilation	on	check with Fisher & Paykel's Customer Care Centre to ensure this	
Electronic oven control	•	Combustible situation	BGRV3-3048H	correctly describes the model currently available. © Fisher & Payl Appliances Ltd 2020	kel
Full extension telescopic sliding shelves	•	Non combustible situation	BGRV2-3048 /	Appliances Eta 2020	
Internal light	true	Recommended hood	BGRV2-1248 HCB48-12_N (48"		
Titanium coated, illuminated metal dials	•	Kecommended 1100d	Professional Range Hood, Dual Blower)	Other product downloads available at fisherpaykel.com	1
			Dual Blower)		

QUICK REFERENCE GUIDE > RGV3-488L Date: 05.07.2024 > 3

 $\overline{\mathbf{\Lambda}}$

Service & Warranty

 $\overline{\mathbf{\Lambda}}$

Revit Gas Range



Rhino Gas Range



User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com