
QUICK REFERENCE GUIDE > CID834DTB4

83cm Series 9 4 Zone Induction Cooktop with Integrated Ventilation

Series 9 | Minimal

Black Glass



A true two-in-one appliance, this cooktop combines the precision of induction cooking with powerful extraction in one seamless, stylish cooktop.

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone

- With nine fan speeds plus boost, select the perfect extraction rate for your cooking
- · Minimal style, sleek black glass finish to suit any kitchen design

DIMENSIONS

Height	218 mm
Width	830 mm
Depth	515 mm

FEATURES & BENEFITS

Seamless Integration

Offering true design freedom, this cooktop can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

Elegant Design

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these cooktops seamlessly blend with other appliances for a cohesive, considered kitchen design.

Precise Control

Fisher & Paykel induction cooktops offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

Effective Extraction

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

Safety Of Induction

Induction cooktops only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it – so they are safer for everyone.

Ease Of Use

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the cooktop surface.

Superior Efficiency

Less heat is wasted during induction cooking because only the cookware is heated, not the cooktop surface. This makes induction cooking more energy-efficient than electric or gas cooktops.

SPECIFICATIONS

Accessories (sold separately)

Recirculation kit	82236 KRCID834 (optional)
Replacement recirculation filter	50182 FRO-DD (optional)
Square grille & butterfly valve for wall exhaust	82393 DO-G-SS (optional)

Cleaning

Dishwasher safe grease filter	•
Flat easy clean glass surface	•

QUICK REFERENCE GUIDE > CID834DTB4

•	Elbow 90° vertical 222x89	82391 E90- V-222-89	Zone ratings	
			Left front	2100W
			Left front zone (PowerBoost set)	3000W
	Performance		Left rear	2100W
•	Gentle heat	•	Left rear zone (PowerBoost set)	3000W
•		q	Right front	2100W
•	-	•	Right front zone (PowerBoost set)	3000W
•		•	Right rear	2100W
		•	Right rear zone (PowerBoost set)	3000W
	SmartZone	•	SmartZone	3700 W
220				
mm H			Zones	
9 + boost	Power requirements			
•	Electrical connection	Terminal block	Number of zones	4
•	Maximum power	7.4 kW		
Side, Rear	Supply frequency	50 Hz		
660 m³/hr	Supply voltage	220 - 240 V	SKU	82228
623 m³/hr				
70 dBA		_		
69 dBA	Product dimensions		The product dimensions and specifications in this page	
192 m³/hr	Depth	515 mm	dimensions and specifications may change at any time.	
38 dBA	Height	218 mm	check with Fisher & Paykel's Customer Care Centre to ensure this page	
	Width	830 mm	Appliances Ltd 2020	ner & r dyker
82389 D1-	Safety		Other product downloads available at fisherpaykel.com	
	Keylock	•		
82392 DA-219-98-150	Pan detection system	•	<u> </u>	
82390 E90-	Safety time out	•	<u> -</u>	a ventilation
H-222-89	Surface hot indicators	•	<u>▼</u>	
	9 + boost Side, Rear 660 m³/hr 623 m³/hr 70 dBA 69 dBA 192 m³/hr 38 dBA 82389 D1- C-222-89 82392 DA-219-98-150 82390 E90-	Performance Gentle heat Heat settings Induction cooking technology Pause function PowerBoost SmartZone 220mm W x 90 mm H 9 + boost Electrical connection Maximum power Side, Rear Supply frequency 660 m³/hr Supply voltage 623 m³/hr 70 dBA 69 dBA Product dimensions 192 m³/hr Depth 38 dBA Height Width 82389 D1- C-222-89 Keylock 82392 DA-219-98-150 Pan detection system 8239. Safety time out	Performance Gentle heat Heat settings 9 Induction cooking technology Pause function PowerBoost SmartZone Power requirements Electrical connection Terminal block Maximum power 7.4 kW Side, Rear Supply frequency So Hz 660 m²/hr Supply voltage 220 - 240 V 623 m²/hr 70 dBA 69 dBA Product dimensions Power Boost Product dimensions Safety C-222-89 Reglace Reglace	Left front Left front Left front zone (PowerBoost set) Left rear Left rear Left rear Left rear Left rear zone (PowerBoost set) Left rear Left rear Left rear zone (PowerBoost set) Right front zone (PowerBoost set) Right front zone (PowerBoost set) Right front zone (PowerBoost set) Right rear zone (PowerBoost set) Right rear zone (PowerBoost set) Right rear zone (PowerBoost set) SmartZone 220mm W x 90 mm H 9 + boost Power requirements Electrical connection Terminal block Maximum power 7.4 kW Side, Rear Supply frequency So Hz 660 m²/hr Supply voltage 220 - 240 V SKU SKU Stay Diply voltage Register and model. Under our policy of continuous im demension and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specifications in this page product and model. Under our policy of continuous im demensions and specification in this page product and model. Under our policy of continuous im demensions and specification in this page product and model. Under our policy of continuous im demensions and specification with page product and model. Under our policy of continuous im demensions and specification with page product and model.

QUICK REFERENCE GUIDE > CID834DTB4



Installation Guide

 $\underline{\downarrow}$

Planning Guide Induction Cooktop with Integrated Ventilation



_____ Rhino-5



Sketchup-8



User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T +65 6741 0777 Wwww.fisherpaykel.com