

Wall Rangehood, 60cm, Telescopic

Series 3 | Contemporary


White

The wall chimney rangehood has contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of 180m³/hr
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

Height	181-185 mm
Width	598 mm
Depth	280 - 460 mm



FEATURES & BENEFITS

Easy Installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Simple To Use

Intuitive controls responds to the touch of your finger. Two halogen spotlights provide clear illumination over the entire cooking surface.

Easy Cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless Integration

With the white glass front panel handles and a brushed stainless steel finish, this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (included)

Aluminium filter	792391
------------------	--------

Accessories (sold separately)

Eave ducting kit	PD-RHK125E
Handle required for recirculation	HS60 Part No.792399
Light bulb	791822
Recirculation carbon filter	792390
Roof ducting kit	PD-RHK125T
Side wall ducting kit	PD-RHK125W

Fan ratings

Maximum air movement	180 m ³ /hr
Maximum sound rating	64 dBA

Installation and cleaning

Air outlet size	100mm (back) and 120mm (top) mm
Dishwasher safe filters	2
Ducted	Top and back extraction

Recirculation **Optional - top and back extraction**

Parts and labour **2 years**



A PEACE OF MIND SALE
 24 Hours 7 Days a Week Customer Support
 T 0800 372 273 Wwww.fisherpaykel.com

Performance

SKU 50015

Extraction type **Surface**
 Fan speeds **2**
 Filter type **Mesh**
 Number of filters **2**

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Power requirements

Other product downloads available at fisherpaykel.com

Supply frequency **50 Hz**
 Supply voltage **220-240 V**

- [↓ Service & Warranty](#)
- [↓ Installation Guide](#)
- [↓ User Guide](#)

Product dimensions

Depth **280 - 460 mm**
 Height **181-185 mm**
 Width **598 mm**

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Product information

Control type **Switch**

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Ventilation features

Light type **LED**

Warranty