QUICK REFERENCE GUIDE > RDV2-488-L\_N
Date: 17.10.2024 > 1

# 48" Series 9 Professional 8 Burner Dual Fuel Range, LPG

Series 9 | Professional

Stainless Steel | LPG



A striking addition to your kitchen, with eight powerful gas burners and two ovens with a combined capacity of 6.9 cu ft.


- · Top burner heat of 19,000 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two convection oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

## **DIMENSIONS**

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "



# **FEATURES & BENEFITS**

#### **Cooktop Power**

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

## **Total Control**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

## Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

## Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

# **Instant Visibility**

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

## Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

# **SPECIFICATIONS**

## Accessories (sold separately)

Square handle option AH-R48

## **Burner ratings**

Maximum burner power	19000 BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front centre (2)	15000BTU

Power front left	19000BTU	Main oven functions		Width	47 7/8 "
Power front right	19000BTU	Bake	•		
Total cooktop power	120000 BTU	Broil	•		
		Clean	•	Rangetop features	
Capacity		Convection bake	•	Sealed range top	•
		Convection broil	•	Vent trim included	•
Shelf positions	5	Number of oven functions	6		
Shelf positions (main oven)	5	Self cleaning	•		
Shelf positions (second oven)	5	True convection	•	Safety	
				Full extension telescopic sliding shelves	•
Cleaning		Oven features			
Pyrolytic self-clean	•	Auto re-ignition system	•	Secondary oven features	
		Internal light	true	Broil	•
		-		Concealed element	•
Controls				Electronic oven control	•
Electric circuit	4 wire	Oven performance		Internal light	•
Metal illuminated dials	•	Bake power	4600		
		Broil	3600 W		
		Main oven - True convection power	2500 W	Secondary oven functions	
Gas Requirements				Bake	•
Fitting and pipe	½ NPT, min. 5⁄8″ ☒ flex line			Number of secondary oven functions	3
Supply Pressure (LPG)	11" to 14" W.C	Power requirements		Proof	•
Supply Plessure (LPO)	11 to 14 W.C	Rated current	50 A		
		Supply frequency	60 Hz		
Main oven features				SKU	71367
Concealed Element	•	Product dimensions			
Electronic oven control	•		20.1/0."		
Internal light	•	Depth	29 1/8 "		
Large broil pan	•	Depth (excluding handles) Height	2918 mm 35 3/4 - 36 3/4 "		
		<b>~</b> ·	<b>, ,</b> -		

QUICK REFERENCE GUIDE > RDV2-488-L N

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020



Date: 17.10.2024 > 3

#### Other product downloads available at fisherpaykel.com

↓ 2D-DWG Dual Fuel Range

↓ 2D-DXF Dual Fuel Range

↓ Data Sheet Dual Fuel Range

↓ Service & Warranty

Installation Guide EN / Guide d'installation FR

Planning Guide Dual Fuel Range

↓ Rhino 5

↓ Sketchup Dual Fuel Range

↓ User Guide EN

Guide d'installation FR

# Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.