QUICK REFERENCE GUIDE > RDV3-486GD-N

48" Series 9 Professional 6 Burner Griddle Dual Fuel Range, Natural Gas

Series 9 | Professional

Stainless Steel | Natural Gas



With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Gas cooktop with griddle and a top burner heat up to 23,500 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities

Use the food probe to monitor your cooking real time

DIMENSIONS

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "

FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 23,500 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories (included) Adjustable feet covers Branded coin end cap Telescopic sliding runners true

Accessories (sold separately)

| Square handle option | AH-R48 |
|----------------------|--------|
|----------------------|--------|

Burner ratings

| Maximum burner power | 23500 BTU |
|----------------------|-----------|
| Power back centre | 18500BTU |
| Power back left | 18500BTU |
| Power back right | 18500BTU |
| Power front centre | 18500BTU |

QUICK REFERENCE GUIDE > RDV3-486GD-N

| Power front left | 23500BTU | Fitting and pipe | ½ NPT, min. 5%" [\] | Oven features | |
|---------------------------------|------------|------------------------------------|---------------------|---|------|
| Power front right | 18500BTU | Complete Decreases (continued as a | flex line | Auto re-ignition system | • |
| Power griddle | 18000BTU | Supply Pressure (natural gas) | 6" to 9" W.C | Concealed element | • |
| Total cooktop power | 134000 BTU | | | Electronic oven control | • |
| | | Main oven features | | Food probe | • |
| | | | | Full extension telescopic sliding shelves | • |
| Capacity | | Concealed Element | • | Internal light | true |
| Shelf positions (main oven) | 5 | Electronic oven control | • | Large broil pan | |
| Shelf positions (second oven) | 5 | Food probe | • | Self-clean proof side racks | • |
| Total capacity (main oven) | 4.8 cu ft | Full extension telescopic racks | • | True convection | • |
| Total capacity second oven | 2.1 cu ft | Internal light | • | | |
| Usable capacity (main oven) | 3.8 cu ft | Large broil pan | • | | |
| | | Self-clean proof side racks | • | Oven functions | |
| | | True convection | • | Air fry | |
| Cleaning | | | | Bake | • |
| Easy clean porcelain basepan | • | Main oven functions | | Classic bake | • |
| Pyrolytic proof shelf runners | • | | | Clean | |
| | | Air fry | • | Convection bake | |
| | | Bake | • | Convection Broil | • |
| Controls | | Classic bake | • | Dehydrate | • |
| Dial with illuminated halo | • | Clean | • | Dehydrate | • |
| Dual control oven dials | • | Convection broil | • | Maxi Broil | • |
| High resolution display | • | Maxi broil | • | Number of functions | 15 |
| Multi-language interface | • | Number of oven functions | 15 | Pastry bake | • |
| Precise cooking with food probe | • | Pizza bake | • | Pizza bake | |
| Recipe and food based functions | • | Rapid proof | • | Rapid proof | |
| Sabbath mode | • | Roast | • | Roast | • |
| Smart appliance | • | Slow cook | • | Slow cook | • |
| Tilting touch screen interface | • | True convection | • | True convection | • |
| - | | Warm | • | Warm | • |
| - | | | | vvgiiii | • |

| Power requirements | | Safety |
|-------------------------------------|--|------------------------------------|
| Connection | 4-prong grounding type [NEMA 14-50P plug] | ADA compliant Child lock |
| Service | 50 A | |
| Supply | 120 / 240 V, 60 Hz | Secondary oven features |
| | · · · | 3/4 Extension racks |
| | | Concealed element |
| Product dimensions | | Electronic oven control |
| Depth | 29 1/8 " | Food probe |
| Height | 35 3/4 - 36 3/4 " | Internal light |
| Width | 47 7/8 " | |
| _ | | Secondary oven functions |
| Rangetop features | | Air fry |
| Sealed range top | • | Bake |
| Vent trim included | • | Classic bake |
| | | Convection bake |
| | | Convection broil |
| Rangetop Performance | | Maxi broil |
| Number of burners | 6 | Number of secondary oven functions |
| Namber of Burners | _ | Pastry bake |
| | | Pizza bake |
| Recommended Back Guards Ventilation | | Rapid proof |
| Combustible situation | BGRV3-3048H | Roast |
| Non combustible situation | BGRV2-3048 / BGRV2-1248 | Warm |
| Recommended hood | HCB48-12_N (48" Professional Range Hood, Dual Blower) | Warranty Parts and labor |

| SKU | 82385 |
|-----|-------|
|-----|-------|

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

Where applicable:

11

Limited 2 years

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

QUICK REFERENCE GUIDE > RDV3-486GD-N

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com