#### Series 3 | Contemporary


White

The wall chimney rangehood has contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of 180m<sup>3</sup>/hr
- Dishwasher safe filters that are easy to remove and clean

# DIMENSIONS

101 105	
181-185 mm	Height
598 mm	Width
280 - 460 mm	Depth



# **FEATURES & BENEFITS**

#### **Easy Installation**

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

#### Simple To Use

Intuitive controls responds to the touch of your finger. Two halogen spotlights provide clear illumination over the entire cooking surface.

#### Easy Cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

### Seamless Integration

With the white glass front panel handles and a brushed stainless steel finish, this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

## SPECIFICATIONS

Accessories (included)				
Aluminium filter	792391			
Accessories (sold separately)				
Eave ducting kit	PD-RHK125E			
Handle required for recirculation	HS60 Part No.792399			
Light bulb	791822			
Recirculation carbon filter	792390			
Roof ducting kit	PD-RHK125T			
Side wall ducting kit	PD-RHK125W			
Fan ratings				
Maximum air movement	180 m³/hr			
Maximum sound rating	64 dBA			
installation and cleaning				
Air outlet size	100mm (back) and 120mm (top) mm			
Dishwasher safe filters	2			
Ducted	Top and back			

Top and back extraction

## QUICK REFERENCE GUIDE > HS60LXW4

Date:	17.10	.2024	> 2
-------	-------	-------	-----

A PEACE OF MIND SALE

24/7

24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com

Recirculation	Optional - top and back extraction	Parts and labour	2 years
Performance		SKU	50015
Extraction type	Surface		
Fan speeds	2	The product dimensions and specifications in this page app	
Filter type	Mesh	product and model. Under our policy of continuous improv dimensions and specifications may change at any time. You	
Number of filters	2	check with Fisher & Paykel's Customer Care Centre to ensu correctly describes the model currently available. © Fisher Appliances Ltd 2020	
Power requirements			
Supply frequency	50 Hz	Other product downloads available at fisherpayke	l.com
Supply voltage	220-240 V		
		↓ Service & Warranty	
		↓ Installation Guide	
Product dimensions		↓ User Guide	
Depth	280 - 460 mm		
Height	181-185 mm	Where applicable:	
Width	598 mm	All appliances use energy, and energy usage typica carbon emissions. <b>Fisher &amp; Paykel Appliances' In-u</b>	se Energy
Product information		Carbon Emissions Estimate indicates carbon emiss product's in-use energy. This is calculated either ar cycle, using the product's market-specific energy la	nually or per
Control type	Switch	consumption data multiplied by the carbon emission energy in your country or region.	ons factor for
Ventilation features		Our In-use Energy Carbon Emissions Estimate is de customers in making informed purchasing decisior	-
Light type	LED	comparing different Fisher & Paykel products. For pump dryer typically has a lower In-use Energy Ca Estimate than a vented dryer.	

Warranty

# FISHER & PAYKEL