QUICK REFERENCE GUIDE > WB24SDEB2

24" Series 9 Minimal Warming Drawer

Series 9 | Minimal

Black



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Minimal design.

- A companion product, designed to match with other Minimal style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- · Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	5 1/2 "
Width	23 7/16 "
Depth	22 5/16 "

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Capacity	
Cappuccino cups	20
Espresso cups	42
Maximum allowable weight	55 lbs
Place settings	6
Usable depth	16 1/16 "
Usable height	3 7/8 "
Usable width	21 1/16 "

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback

Automatic timers

30', 45', 1h, 2h, 4h, 6h

Electronic capacitive touch controls

On/Off indicator

Pre-set heating functions

Push-to-open drawer

Soft close drawer

Standby mode

Functions

Cups • Dehydrate •

QUICK REFERENCE GUIDE > WB24SDEB2

6
•
•
•
•

Performance

Heated glass base and fan

Low temperature cooking

Temperature levels

Temperature range

•

95°F-185°F

Power Requirements

Amperage	10 A
Power outlet	3-prong grounding-type
Supply frequency	60 Hz
Supply voltage	110 V

Product Dimensions

Adjustable front door panel to align with	
surrounding cabinetry	

Depth	22 5/16 "
Height	5 1/2 "
Width	23 7/16 "

Safety

Automatic turn off after 12 hours

Full extension slides •

SKU 82141

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

_	
$\underline{\downarrow}$	2D-DXF Warming Drawer
$\underline{\downarrow}$	Archicad Warming Drawer
\underline{ullet}	Data Sheet Warming Drawer
$\underline{\downarrow}$	Service & Warranty
$\underline{\downarrow}$	Installation Guide Companion Products EN
$\underline{\downarrow}$	Installation Guide
$\overline{\bot}$	Revit Warming Drawer
$\underline{\downarrow}$	Rhino Warming Drawer
$\underline{\downarrow}$	Sketchup Warming Drawer
\underline{ullet}	Guide d'utilisation FR
$\overline{\downarrow}$	User Guide

2D-DWG Warming Drawer

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



FISHER & PAYKEL