
QUICK REFERENCE GUIDE > CID834DTB4

Induction Cooktop, 83cm, 4 Zones with Integrated Ventilation

Series 9 | Minimal

Black Glass



A true two-in-one appliance, this cooktop combines the precision of induction cooking with powerful extraction in one seamless, stylish cooktop.

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone

- With nine fan speeds plus boost, select the perfect extraction rate for your cooking
- · Minimal style, sleek black glass finish to suit any kitchen design

DIMENSIONS

Height 218 mm
Width 830 mm
Depth 515 mm

FEATURES & BENEFITS

Seamless Integration

Offering true design freedom, this cooktop can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

Elegant Design

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these cooktops seamlessly blend with other appliances for a cohesive, considered kitchen design.

Precise Control

Fisher & Paykel induction cooktops offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

Effective Extraction

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

Safety Of Induction

Induction cooktops only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it – so they are safer for everyone.

Ease Of Use

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the cooktop surface.

Superior Efficiency

Less heat is wasted during induction cooking because only the cookware is heated, not the cooktop surface. This makes induction cooking more energy-efficient than electric or gas cooktops.

SPECIFICATIONS

Accessories (sold separately)

(optional)	Recirculation kit
50182 FRO-DD (optional)	Replacement recirculation filter
82393 DO-G-SS (optional)	Square grille & butterfly valve for wall exhaust

Cleaning

Dishwasher safe grease filter

Flat easy clean glass surface	•	Elbow 90° vertical 222x89	82391 E90- V-222-89	Warranty	
Flush grille	•		V-222-03	Parts and labour	2 years
Controls		Performance		7	
A		Gentle heat	•	Zone ratings	
Auto cut-off timer for each zone	•	Heat settings	9	Left front	2100W
Minute timer	•	Induction cooking technology	•	Left front zone (PowerBoost set)	3000W
Soft-touch electronic controls	•	Pause function	•	Left rear	2100W
Touch and slide controls	•	PowerBoost	•	Left rear zone (PowerBoost set)	3000W
		SmartZone	•	Right front	2100W
		omarizone -		Right front zone (PowerBoost set)	3000W
Downdraft performance				Right rear	2100W
Air outlet size	220mm W x 90 mm H	Power requirements		Right rear zone (PowerBoost set)	3000W
Air speeds	9 + boost	Electrical connection	Terminal block	SmartZone	3700 W
Brushless motor	•	Maximum power	7.4 kW		
Ducted externally	•	Supply frequency	50 Hz	_	
Ducting direction	Side, Rear	Supply voltage	220 - 240 V	Zones	
Maximum air flow (Boost)	660 m³/hr			Number of zones	4
Maximum air flow (Level 9)	623 m³/hr				
Maximum noise level (Boost)	70 dBA	Product dimensions			
Maximum noise level (Level 9)	69 dBA	Depth	515 mm	SKU	82228
Minimum air flow	192 m³/hr	Height	218 mm		
Minimum noise level	38 dBA	Width	830 mm		
				The product dimensions and specifications in this page	
				product and model. Under our policy of continuous imp dimensions and specifications may change at any time.	
Ducting Accessories (optional)		Safety		check with Fisher & Paykel's Customer Care Centre to ensure this page	
Duct 1m Connector 222x89	82389 D1-	Keylock	•	correctly describes the model currently available. © Fisl Appliances Ltd 2020	ner & Paykel
	C-222-89	Pan detection system	•	••	
Ducting adaptor	82392 DA-219-98-150	Safety time out	•		
Elbow 90° horizontal 222x89	82390 E90- H-222-89	Surface hot indicators	•	Other product downloads available at fisherpaykel.com	

QUICK REFERENCE GUIDE > CID834DTB4

- $\overline{\mathbf{\Lambda}}$
- 2D DWG Induction Cooktop with Integrated Ventilation
- 2D DXF Induction Cooktop with Integrated Ventilation
- ↓ Archicad-23
- ↓ Service & Warranty
- ↓ Installation Guide
- ↓ Planning Guide Induction Cooktop with Integrated Ventilation
- ↓ Revit 18
- ↓ Rhino-5
- ↓ Sketchup-8
- Specification Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1300 650 590 Wwww.fisherpaykel.com