QUICK REFERENCE GUIDE > OR90SPI6X1 Date: 17.12.2024 > 1

90cm Series 9 Professional 5 Zone Induction Pyrolytic Cooker, 2 SmartZones

Series 9 | Professional

Stainless Steel



Professional style and performance, with a large oven and five cooktop zones that can be paired to create an expansive cook zone.

- Large convection oven with 140L total capacity
- Nine functions plus Rotisserie, including Pastry Bake, Pizza Mode and Rapid Proof
- Non-tip full-extension shelves for safe removal of hot dishes

 Pyrolytic self-cleaning oven cycle breaks down food residue for an easy clean

DIMENSIONS

 Height
 898-946 mm

 Width
 897 mm

 Depth
 600 mm

FEATURES & BENEFITS

Multi-Shelf Cooking

Our AeroTech™ system circulates heat evenly for a consistent temperature throughout the cavity, helping you achieve perfect results even when using multiple shelves.

Quality And Durability

Every detail has been carefully crafted. The solid, perfectly balanced soft-close door, durable cooktop and glowing halo dials all add up to a premium freestanding cooker.

Power & Control

Instant and immediate control from the highest to the gentlest heat. The finely tuned cooktop controls let you sear, stir fry or simmer a delicate sauce to perfection.

Easy To Clean

Cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new. The pyrolytic self-clean oven cycle breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth.

Even Heat

Accurate, electronically controlled oven heat ensures a great result every time.

Large Capacity Oven

The generous 140L total capacity oven gives you plenty of space to cook multiple dishes at once.

SPECIFICATIONS

Accessories (included)

1
2 sets (part 578744)
1 set
1 set
1 set
•

Accessories (sold separately)

Kick strip, stainless steel (optional)	KICKOR90X1
--	------------

Capacity

Shelf positions	6
Total capacity	140 L
Usable capacity	120 L

Cleaning

Acid resistant graphite enamel	•
Drop down grill element	
Flat easy clean glass surface	

QUICK REFERENCE GUIDE > OR90SPI6X1 Date: 17.12.2024 > 2

	Power requirements		Oven features	•	Pyrolytic proof shelf runners
68 A	Amperage	•	AeroTech™ technology	•	Pyrolytic self-clean
50 Hz	Supply frequency	•	Automatic rapid pre-heat	•	Removable oven door
220-240 V	Supply voltage	•	Convection	•	Removable oven door inner glass
		•	Electronic oven control	•	Removable shelf runners
		•	Full extension telescopic sliding shelves		
	Product dimensions	4 x 25W halogen (2 side & 2 top)	Internal light		Controls
600 mm	Depth	•	Soft open/close door	•	Audio feedback
898-946 mm	Height	•	Twin cavity fans	•	Automatic cooking/minute timer
897 mm	Width	•	Warming drawer		Automatic pre-set temperatures
			-	•	Celsius/Fahrenheit temperature
	Rangetop features	_		•	Dial with illuminated halo
			Oven functions	•	Electronic clock
•	Dual colour display	•	Bake	•	High resolution display
•	Gentle heat	•	Fan bake	•	Laser etched graphics
9	Heat settings	•	Fan forced	•	Precise electronic temperature control
•	Hob rail	•	fanGrill	•	Sabbath mode
60 mm	Hob rear trim	•	Grill	•	Toughened fused glass graphics
•	Induction cooking technology	9 + rotisserie	Number of functions	•	Turned stainless steel clock buttons
true	PowerBoost	•	Pastry Bake with Pizza mode	•	Turned stainless steel clock crown (dial)
true	SmartZone	•	Pyrolytic self-clean		
•	Zone bridging	•	Rapid proof		
		•	Roast		Installation Dimensions
	Rangetop Performance	•	Rotisserie	600 mm	Installation cutout dimensions (Depth)
2300 W	Centre			900 mm	Installation cutout dimensions (Width)
1600 (1850) W	Left front zone rating				
2100 (3000) W	Left rear zone rating		Oven performance		
5	Number of cooking zones	Quadruple glazed	CoolTouch door		Main oven features
3000	PowerBoost	4500W	Grill power	•	Internal light
1600 (1850) W	Right front zone rating	202 W	Warming drawer power		

QUICK REFERENCE GUIDE > OR90SPI6X1 Date: 17.12.2024 > 3

Right rear zone rating

2100 (3000) W

Safety

Advanced cooling system

Anti-tilt bracket

Balanced oven door

Catalytic venting system

Child lock

CoolTouch door

Full extension telescopic sliding shelves

Non-tip shelves

Pan detection system

Safety time out

Warranty

Spill containment

Spillage auto off

Surface hot indicators

Parts and labour	2 years

SKU 82724

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Where applicable:

1.2 L

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

