
QUICK REFERENCE GUIDE > CID834DTB4

# 83cm Series 9 4 Zone Induction Cooktop with Integrated Ventilation

Series 9 | Minimal

Black Glass



A true two-in-one appliance, this cooktop combines the precision of induction cooking with powerful extraction in one seamless, stylish cooktop.

- Seamless kitchen integration, without the need for overhead ventilation
- Four cooking zones, including simple pairing of two zones to create a SmartZone

- With nine fan speeds plus boost, select the perfect extraction rate for your cooking
- · Minimal style, sleek black glass finish to suit any kitchen design

# **DIMENSIONS**

| Height | 218 mm |
|--------|--------|
| Width  | 830 mm |
| Depth  | 515 mm |

# **FEATURES & BENEFITS**

# **Seamless Integration**

Offering true design freedom, this cooktop can be placed anywhere – eliminating the need for bulky overhead ventilation and helping to create a seamless flow between kitchen and living spaces. Installed raised or flush, it's perfect for islands, or homes with high ceilings.

# **Elegant Design**

The subtle black glass and durable matte black detailing blend elegance with durability. With premium styling, these cooktops seamlessly blend with other appliances for a cohesive, considered kitchen design.

# **Precise Control**

Fisher & Paykel induction cooktops offer extremely accurate temperature control from very high to very low heats, so you can sear, sauté and temper like a pro. Touch&Slide controls react immediately when you adjust the temperature, so you can go from a boil to a simmer in seconds.

# Effective Extraction

Designed for busy homes, the integrated ventilation works effectively and unobtrusively in the background. Featuring nine fan speeds, plus a boost function, for quickly removing odours and steam.

# Safety Of Induction

Induction cooktops only start heating your pot or pan once you've placed it on the surface and stop as soon as you remove it – so they are safer for everyone.

# Ease Of Use

Designed for simple removal, the grease filter tray effectively captures spills, while the single glass cooking surface can be easily wiped clean. A flush ventilation grille allows pots to effortlessly slide across the cooktop surface.

# Superior Efficiency

Less heat is wasted during induction cooking because only the cookware is heated, not the cooktop surface. This makes induction cooking more energy-efficient than electric or gas cooktops.

# **SPECIFICATIONS**

# Accessories (sold separately)

| Recirculation kit                                | 82236 KRCID834<br>(optional) |
|--|------------------------------|
| Replacement recirculation filter                 | 50182 FRO-DD<br>(optional)   |
| Square grille & butterfly valve for wall exhaust | 82393 DO-G-SS<br>(optional)  |

### Cleaning

| Dishwashe | er safe | grease | filter |  | • |
|-----------|---------|--------|--------|--|---|
|           |         |        |        |  |   |

Flat easy clean glass surface •

QUICK REFERENCE GUIDE > CID834DTB4

| •                      | Elbow 90° vertical 222x89   | 82391 E90-<br>V-222-89  | Zone ratings   |  |  |
|------------------------|---|---|--|--|--|
|                        |   |   | Left front   | 2100W  |  |
|                        |   |   | Left front zone (PowerBoost set)   | 3000W  |  |
|                        | Performance   |   | Left rear  | 2100W  |  |
| •                      | Gentle heat   | •   | Left rear zone (PowerBoost set)  | 3000W  |  |
| •                      |   | q   | Right front  | 2100W  |  |
| •                      | -   | •   | Right front zone (PowerBoost set)  | 3000W  |  |
| •                      |   | •   | Right rear   | 2100W  |  |
|                        |   | •   | Right rear zone (PowerBoost set)   | 3000W  |  |
|                        | SmartZone   | •   | SmartZone  | 3700 W   |  |
| 220                    |   |   |  |  |  |
| mm H                   |   |   | Zones  |  |  |
| 9 + boost              | Power requirements  |   |  |  |  |
| •                      | Electrical connection   | Terminal block  | Number of zones  | 4  |  |
| •                      | Maximum power   | 7.4 kW  |  |  |  |
| Side, Rear             | Supply frequency  | 50 Hz   |  |  |  |
| 660 m³/hr              | Supply voltage  | 220 - 240 V   | SKU  | 82228  |  |
| 623 m³/hr              |   |   |  |  |  |
| 70 dBA                 |   | _   |  |  |  |
| 69 dBA                 | Product dimensions  |   | The product dimensions and specifications in this page   |  |  |
| 192 m³/hr              | Depth   | 515 mm  | dimensions and specifications may change at any time.  |  |  |
| 38 dBA                 | Height  | 218 mm  | check with Fisher & Paykel's Customer Care Centre to e   |  |  |
|                        | Width   | 830 mm  | Appliances Ltd 2020  | ner & r dyker  |  |
|                        |   |   |  |  |  |
| 82389 D1-              | Safety  |   | Other product downloads available at fisherpaykel.com  |  |  |
|                        | Keylock   | •   |  |  |  |
| 82392<br>DA-219-98-150 | Pan detection system  | •   | <u> </u>   |  |  |
| 82390 E90-             | Safety time out   | •   | <u> -</u>  | a ventilation  |  |
| H-222-89               | Surface hot indicators  | •   | <u>▼</u>   |  |  |
|                        |   |   |  |  |  |
|                        | 9 + boost  Side, Rear 660 m³/hr 623 m³/hr 70 dBA 69 dBA 192 m³/hr 38 dBA  82389 D1- C-222-89 82392 DA-219-98-150 82390 E90- | Performance Gentle heat Heat settings Induction cooking technology Pause function PowerBoost SmartZone  220mm W x 90 mm H 9 + boost Electrical connection Maximum power Side, Rear Supply frequency 660 m³/hr Supply voltage  623 m³/hr 70 dBA 69 dBA Product dimensions 192 m³/hr Depth 38 dBA Height Width  82389 D1- C-222-89 Keylock 82392 DA-219-98-150 Pan detection system 8239. Safety time out | Performance   Gentle heat   Heat settings   9   Induction cooking technology   Pause function   PowerBoost   SmartZone   Power requirements   Electrical connection   Terminal block   Maximum power   7.4 kW   Side, Rear   Supply frequency   So Hz   660 m²/hr   Supply voltage   220 - 240 V   623 m²/hr   70 dBA   69 dBA   Product dimensions   Power Boost   Product dimensions   Safety   C-222-89   Reglace   Reglace | Left front Left front Left front zone (PowerBoost set) Left rear zone (PowerBoost set) Right front zone (PowerBoost set) Right front zone (PowerBoost set) Right front zone (PowerBoost set) Right rear zone (PowerBoost set) Right rear zone (PowerBoost set) Right rear zone (PowerBoost set) SmartZone  220mm W x 90 mm H 9 + boost Power requirements Left rear Right rear zone (PowerBoost set) SmartZone  220ms W x 90 mm H 9 + boost Left rear Right rear Right rear Right rear zone (PowerBoost set) SmartZone  220ms Number of zones Number |  |

QUICK REFERENCE GUIDE > CID834DTB4 Date: 17.12.2024 > 3



Installation Guide

 $\underline{\downarrow}$ 

Planning Guide Induction Cooktop with Integrated Ventilation



\_ ↓ Rhino-5



Sketchup-8



User Guide

# Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T +65 6741 0777 Wwww.fisherpaykel.com