

# Wall Rangehood, 90cm, Pyramid Chimney

Series 7 | Classic

White



Pairing well with the white Classic Freestanding Cooker, this wall chimney rangehood extracts steam and cooking odours effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- Dishwasher-safe filters that are easy to remove and clean
- Powerful 780m<sup>3</sup>/hr maximum airflow with edge-to-edge extraction
- Energy-efficient LED lighting to illuminate your cooktop

## DIMENSIONS

Height	636-975 mm
Width	898 mm
Depth	500 mm

## FEATURES & BENEFITS

### Complementary Design

This wall chimney rangehood is designed to match the white Classic Freestanding Cooker in both colour and style, including stylish chrome touch buttons.

### Cleaner Air

Odours can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 780m<sup>3</sup>/hr, this rangehood removes cooking odours effectively, as well as grease and steam while cooking.

### Intuitive Controls

Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

### Simple To Clean

Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

### Design Quality

Made from quality stainless steel with an excellent finish and robust product design, this rangehood is both visually appealing and durable.

### Considered Efficiency

The extraction rate ensures interior air and climate is not excessively removed to the outside, while LED lighting on the rangehood has been chosen for energy efficiency.

### Easy Installation

This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Freestanding Cooker. It can be either externally ducted or internally recirculated, for simple installation

## SPECIFICATIONS

### Accessories (included)

Aluminium filter	792564
------------------	--------

### Accessories (sold separately)

Chimney extension	793224
Eave ducting kit	PD-RHK 150E
Light bulb	792556
Recirculation carbon filter	792481
Recirculation diverter	792560
Roof ducting kit	PD-RHK 150T
Side wall ducting kit	PD-RHK 150W

### Fan ratings

Maximum air movement	780 m <sup>3</sup> /hr
Speed 3 sound rating	65 dBA

### Installation and cleaning

Air outlet size	150 mm
-----------------	--------

Dishwasher safe filters	<b>3</b>
Ducted	<b>Vertical only</b>
Recirculation	<b>Optional</b>
Stainless steel filter cover	•
Two piece height adjustable flue	•

### Performance

Extraction type	<b>Surface</b>
Fan speeds	<b>3</b>
Filter type	<b>Mesh</b>
Number of filters	<b>3</b>

### Power requirements

Lighting power	<b>8 W</b>
Supply frequency	<b>50 Hz</b>
Supply voltage	<b>230 V</b>

### Product dimensions

Depth	<b>500 mm</b>
Height	<b>636-975 mm</b>
Width	<b>898 mm</b>

### Product information

Control type	<b>Classic style chrome touch buttons</b>
--------------	---

### Ventilation features

Light type	<b>LED</b>
------------	------------

### Warranty

Parts and labour	<b>2 years</b>
------------------	----------------

SKU	<b>50154</b>
-----	--------------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

### Other product downloads available at [fisherpaykel.com](http://fisherpaykel.com)

- [↓ Archicad Wall Rangehood](#)
- [↓ Service & Warranty](#)
- [↓ Installation Guide](#)
- [↓ Revit Wall Rangehood](#)
- [↓ Rhino Wall Rangehood](#)
- [↓ Sketchup Wall Rangehood](#)
- [↓ User Guide](#)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



**A PEACE OF MIND SALE**  
**24 Hours 7 Days a Week Customer Support**

T 0800 372 273 W [www.fisherpaykel.com](http://www.fisherpaykel.com)