QUICK REFERENCE GUIDE > HP90IDCHX4

Integrated Insert Rangehood, 90cm

Series 7 | Integrated

Stainless Steel and Glass



With edge-to-edge extraction, this rangehood is perfectly hidden away in your cabinetry.


- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful maximum air movement of 780m³/hr
- Energy-efficient LED lighting to illuminate your cooking surface
- Wi-Fi enabled for notifications through the SmartHQ[™] app

DIMENSIONS

Height 316 mm

Width 830 mm

Depth 280 mm



FEATURES & BENEFITS

Achieve The Invisible

This stylish rangehood fits seamlessly into your kitchen cabinetry, providing ventilation that is as discreet as it is powerful.

Effective Extraction

Featuring three fan speeds, plus a boost function, this rangehood provides powerful extraction to quickly remove odours and steam. Odours can linger in the kitchen well after cooking is finished so the timer keeps the hood working for up to 15 minutes before automatically turning off.

Easy Cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe, while the glass and stainless steel finish is easily wiped clean. The SmartHQ $^{\text{TM}}$ app will notify you when to clean the filter to ensure you get the best performance out of your rangehood.

Quality Materials

This rangehood comes in a sleek black glass finish with a real stainless steel frame.

Full Surface Lighting

Low energy, dimmable LED lights provide superb illumination of the entire cooking surface.

SPECIFICATIONS

Accessories (included)

Aluminium filter 792943

Accessories (sold separately)

Eave ducting kit	PD-RHK150E
Light bulb	requires service to replace
Recirculation carbon filter	793599
Roof ducting kit	PD-RHK150T
Side wall ducting kit	PD-RHK150W

QUICK REFERENCE GUIDE > HP90IDCHX4

Fan ratings		
Maximum air movement	780 m³/hr	
Installation and cleaning		
Air outlet size	150 & 120 mm	
Dishwasher safe filters	2	
Ducted	Top extraction	
Recirculation	Optional - top extraction	
Performance		
Extraction type	Perimeter	
Fan speeds	3	
Fan speeds + boost	•	
Filter type	Mesh with perimeter extraction	
Number of filters	2	
Power requirements		
Supply frequency	50 Hz	
Supply voltage	220 - 240 V	
Product dimensions		
Depth	280 mm	
Height	316 mm	
Width	830 mm	

Product information

Control type Capacitive touch

Ventilation features

Auto-off/Run-on timer	•
Dimmable lights	•
Filter cleaning alert	•
Light type	LED strip
Timer function	•
Wi-Fi connectivity	•

Warranty

Parts and labour	2 years
SKU	50190

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



2D-DWG Insert Rangehood



2D-DXF Insert Rangehood



Data Sheet Insert Rangehood



Service & Warranty



Installation Guide Integrated Insert Rangehood



Preliminary Specification Guide Rangehood



User Guide Integrated Insert Rangehood

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com