QUICK REFERENCE GUIDE > RHV3-484-N

48" Series 11 Professional 4 Burner + 4 Zone Hybrid Self-Cleaning Range, NG

Series 11 | Professional

Stainless Steel | Natural Gas




With both induction and gas cooktops and two convection ovens, you're ready to create a feast - guided by an intuitive touchscreen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 23,500 BTU, for seriously fast boiling
- Four induction cooking zones, which can be paired to form two SmartZones

• 6.9 cu ft total oven capacity across two oven cavities

DIMENSIONS

Height	35 3/4 - 36 3/4 "		
Width	47 7/8 "		
Depth	29 1/8 "		



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

On the gas side of the cooktop, Sealed dual flow burners deliver power up to 23,500 BTU, while the induction side delivers up to 3700W. This finely tuned cooktop provides instant and immediate control from the highest heat to the most gentle simmer.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, high-quality glass, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function. The induction zones only need a quick wipe after use to keep them clean.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers

QUICK REFERENCE GUIDE > RHV3-484-N Date: 17.10.2024 > 2

Branded coin end cap	•	Dual control oven dials	•	Maxi broil	•
		Electric circuit	4 wire	Number of oven functions	15
		High resolution display	•	Pizza bake	•
Accessories (sold separately)		Metal illuminated dials	•	Rapid proof	•
Square handle option AH-R48	AH-R48	Multi-language interface	•	Roast	•
		Precise cooking with food probe	•	Self cleaning	•
		Recipe and food based functions	•	Slow cook	•
Burner ratings		Sabbath mode	•	True convection	•
Maximum burner power	23500 BTU	Smart appliance	•	Warm	•
Power back left	18500BTU	Tilting touch screen interface	•		
Power back right	18500BTU				
Power front left	23500BTU			Oven features	
Power front right	18500BTU	Gas Requirements		Auto re-ignition system	•
Total cooktop power	79000 BTU	Fitting and pipe	½ NPT, min. 5%" 🛭	Concealed element	•
			flex line	Electronic oven control	•
		Supply Pressure (natural gas)	6" to 9" W.C	Full extension telescopic sliding shelves	•
Capacity				Internal light	true
Shelf positions (main oven)	5	Main oven features		True convection	•
Shelf positions (second oven)	5				
Total capacity (main oven)	4.8 cu ft	Concealed Element	•		
Total capacity second oven	2.1 cu ft	Electronic oven control	•	Oven functions	
Usable capacity (main oven)	3.8 cu ft	Full extension telescopic racks	•	Air fry	•
		Internal light	•	Bake	•
		True convection	•	Classic bake	•
Cleaning				Clean	•
Easy clean porcelain basepan	•	Main oven functions		Convection bake	•
Pyrolytic self-clean	•			Convection Broil	•
		Air fry	•	Dehydrate	•
		Bake	•	Dehydrate	•
Controls		Classic bake	•	Maxi Broil	•
Dial with illuminated halo	•	Clean	•	Number of functions	15
		Convection broil	•		

QUICK REFERENCE GUIDE > RHV3-484-N Date: 17.10.2024 > 3

Pastry bake	•	Gentle heat	•	Safety time out	•
Pizza bake	•	Heat settings	9	Surface hot indicators	•
Rapid proof	•	Induction cooking technology	•		
Roast	•	Sealed range top	•		
Slow cook	•	SmartZone	2	Secondary oven features	
True convection	•	Vent trim included	•	3/4 Extension racks	2
Warm	•	Zone bridging	•	Electronic oven control	•
				Food probe	•
			_	Internal light	•
Oven performance		Rangetop Performance			
Bake	4600 W	Left front zone rating	2100 (3700) W		
Broil	3600 W	Left rear zone rating	2100 (3700) W	Secondary oven functions	
Broil power	4000 W	Number of burners	4	Air fry	•
Main oven - True convection power	2500 W	Number of cooking zones	4	Bake	•
		PowerBoost	•	Classic bake	•
		PowerBoost all zones	up to 3700 W	Convection bake	•
Power requirements		Right front zone rating	2100 (3700) W	Convection broil	•
Connection	4-prong	Right rear zone rating	2100 (3700) W	Maxi broil	•
	grounding type [NEMA 14-50P			Number of secondary oven functions	11
	plug]			Pastry bake	•
Service	50 A	Recommended Back Guards Ventilation		Pizza bake	•
Supply	120 / 240 V, 60 Hz	Combustible situation	BGRV3-3048H	Rapid proof	•
	112	Non combustible situation	BGRV2-3048 /	Roast	•
			BGRV2-1248	Warm	•
Product dimensions		Recommended hood	HCB48-12_N (48" Professional		
Depth	29 1/8 "		Range Hood, Dual Blower)		
Height	35 3/4 - 36 3/4 "		Budi Blowery	Warranty	
Width	47 7/8 "			Parts and labor	Limited 2 years
MIMUI	47 7/0	Safety			
		ADA compliant	•		
Rangetop features		Pan detection system		SKU	82792

QUICK REFERENCE GUIDE > RHV3-484-N Date: 17.10.2024 > 4

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

2D-DWG Dual Fuel Cooker with Backguard BGRV2-1248

↓ 2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048

2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim

↓ 2D-DWG Dual Fuel Range

↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-1248

↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048

↓ 2D-DXF Dual Fuel Range

↓ Service & Warranty

Planning Guide Professional Style Dial/Handle Accessories

↓ Rhino Dual Fuel Cooker

J. Sketchup Dual Fuel Cooker

↓ User Guide

↓ Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com