48" Series 9 Professional 5 Burner + Griddle Dual Fuel Self-Cleaning Range, LPG

| Series 9 | Professional |
|----------|--------------|

Stainless Steel | LPG




With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Gas cooktop with a griddle and five burners that deliver up to 19,000 BTU for fast boiling
- 6.9 cu ft total oven capacity across two oven cavities

Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

| Height | 35 3/4 - 36 3/4 " |
|--------|-------------------|
| Width | 47 7/8 " |
| Depth | 29 1/8 " |



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 19,000 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers

Branded coin end cap

QUICK REFERENCE GUIDE > RDV3-485GD-L

Accessories (sold separately)

| Square handle option | AH-R48 |
|----------------------|--------|
| | |

Burner ratings

| Maximum burner power | 19000 BTU |
|----------------------|-----------|
| Power back left | 11500BTU |
| Power back right | 11500BTU |
| Power centre | 19000BTU |
| Power front left | 15000BTU |
| Power front right | 15000BTU |
| Power griddle | 24000BTU |
| Total cooktop power | 96000 BTU |

Capacity

| Shelf positions (main oven) | 5 |
|-------------------------------|-----------|
| Shelf positions (second oven) | 5 |
| Total capacity (main oven) | 4.8 cu ft |
| Total capacity second oven | 2.1 cu ft |
| Usable capacity (main oven) | 3.8 cu ft |

Cleaning

Electric circuit4 wireHigh resolution display•Metal illuminated dials•Multi-language interface•Precise cooking with food probe•recipeAndFoodBasedFunctions•Sabbath mode•Smart appliance•Tilting touch screen interface•

Gas Requirements

| Fitting and pipe | ½ NPT, min. ⁵‰″ ⊠ flex line |
|-----------------------|--------------------------------|
| Supply Pressure (LPG) | 11" to 14" W.C |

Main oven features

| Concealed Element | |
|---------------------------------|--|
| Electronic oven control | |
| Full extension telescopic racks | |
| Internal light | |
| Large broil pan | |
| Self-clean proof side racks | |

Main oven functions Air fry Bake Classic bake Clean

Convection bake

reConvection broil•Maxi broil•Number of oven functions15Pizza bake•Pizza bake•Rapid proof•Roast•Slow cook•True convection•Warm•

Oven features

| Auto re-ignition system | • |
|---|------|
| Concealed element | • |
| Electronic oven control | • |
| Full extension telescopic sliding shelves | • |
| Internal light | true |
| Titanium coated, illuminated metal dials | • |

Oven functions

.

| Air fry | • | |
|---------------------|----|--|
| Bake | • | |
| Classic bake | • | |
| Clean | • | |
| Convection bake | • | |
| Convection Broil | • | |
| Dehydrate | • | |
| Dehydrate | • | |
| Maxi Broil | • | |
| Number of functions | 15 | |
| | | |

QUICK REFERENCE GUIDE > RDV3-485GD-L

| Pastry bake | | |
|-----------------|--|--|
| Pizza bake | | |
| Rapid proof | | |
| Roast | | |
| Slow cook | | |
| True convection | | |
| Warm | | |
| | | |

| Oven performance | е |
|------------------|---|
|------------------|---|

| Bake power | 4600 |
|-----------------------------------|--------|
| Broil | 3600 W |
| Main oven - True convection power | 2500 W |

Power Requirements

| Connection | 4-prong grounding type [NEMA 14-50 plug] |
|---------------------------|---|
| Service | 50 A |
| Supply | 120 / 240 V, 60 Hz |
| | |
| Product Details | |
| Self Cleaning Sf | Yes |
| | |
| Product Dimensions | |
| Depth | 29 1/8 " |
| Depth (excluding handles) | 2918 mm |
| Height | 35 3/4 - 36 3/4 " |

| Width | 47 7/8 " |
|-------------------------------------|---|
| Rangetop features | |
| Sealed range top | |
| Vent trim included | • |
| Recommended Back Guards Ventilation | |
| Combustible situation | BGRV3-3048H |
| Non combustible situation | / BGRV2-3048 BGRV2-1248 |
| Recommended hood | HCB48-12_N (48''' Professional Range Hood, Dual Blower) |
| Safety | |
| ADA compliant | |
| Secondary oven features | |
| 3/4 Extension racks | 2 |
| Concealed element | |
| Electronic oven control | • |
| Food probe | • |
| Internal light | |
| Secondary oven functions | |
| Air fry | |
| | |

| Bake | • |
|------------------------------------|----|
| Classic bake | • |
| Convection bake | • |
| Convection broil | • |
| Maxi broil | • |
| Number of secondary oven functions | 11 |
| Pastry bake | • |
| Pizza bake | • |
| Rapid proof | • |
| Roast | • |
| Warm | • |
| | |

Date: 17.10.2024 > 3

81895

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

| <u> </u> |
|----------|
| |

- 2D-DXF Dual Fuel Range $\overline{\mathbf{1}}$
- ArchiCAD Dual Fuel Range $\overline{\mathbf{1}}$
- $\overline{\mathbf{1}}$ Service & Warranty

SKU

- Planning Guide Professional Style Dial/Handle Accessories \downarrow
- Revit Dual Fuel Range $\overline{\mathbf{1}}$
- Rhino Dual Fuel Range $\mathbf{1}$
- SketchUp Dual Fuel Range $\mathbf{1}$

↓ User Guide EN

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com