# 60cm Series 7 Contemporary Pyrolytic Oven, 16 Function

Series 7 | Contemporary

#### Stainless Steel




With beautiful Contemporary styling and a generous 85L total capacity, this built-in oven helps to ensures that every dish you create is cooked to perfection.

- 16 oven functions including Pastry Bake, Roast, Dehydrate and Rapid Proof
- Moisture level control with ActiveVent technology

- Pyrolytic self-cleaning function breaks down food residue for an easy clean
- Guided cooking capability offers helpful tips for different food types

### DIMENSIONS

Height	598 mm
Width	596 mm
Depth	565 mm



# **FEATURES & BENEFITS**

Multi-Function Flexibility

Each function has been perfected to ensure that no matter what you're cooking, you've got the right heat to match. This built-in oven has 16 functions including Pastry Bake, Roast, Fan Grill, Dehydrate and Rapid Proof, allowing you to use a variety of cooking styles.

#### **Generous Capacity**

With a generous 85L total capacity, you can create several perfectly cooked dishes at once using multiple shelves.

#### Cook With Confidence

The intuitive 2.4" screen provides an intuitive guided cooking experience that helps to deliver perfect results, whether you've been cooking all your life or are just starting out. Cook by food type and allow your oven to guide you through steps, or change temperature and heat type automatically, depending on your selection.

#### Exceptional performance

Our unique cooking technologies were developed to deliver perfect results. ActiveVent ensures optimised moisture levels, while AeroTech<sup>™</sup> circulates heat evenly for a consistent temperature.

#### Self-Cleaning

Pyrolytic self-clean breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth. The enamel coated side racks don't need to be removed when using this function.

#### **Design Freedom**

Designed to fit seamlessly into your kitchen, this built-in oven features premium materials and detailing to support a cohesive, considered kitchen design.

#### Safe And Sound

The CoolTouch door features triple glazing and a cooling system that ensures it's safe to touch from the outside – protecting both your hands and the surrounding cabinetry.

# SPECIFICATIONS

#### Accessories (included)

Full extension sliding shelves	1 set
Grill rack	1 set
Pyrolytic proof shelf runners	•
Roasting dish	1
Smokeless grill tray	1
Step down wire shelf	1
Wired temperature sensor	1

#### Capacity

6
85 L
72 L

#### Cleaning

Acid resistant graphite enamel	
Pyrolytic proof shelf runners	
Pyrolytic self-clean	
Removable oven door	
Removable oven door inner glass	
Removable shelf runners	

#### Controls

Adjustable audio and display settings	
Audio feedback	
Automatic cooking/minute timer	

Automatic pre-set temperatures	
Celsius/Fahrenheit temperature	
Certified Sabbath mode	
Delay start	
Electronic clock	
Electronic oven control	
Food probe	
Guided cooking by food types	
Halogen lights	
Intuitive touchscreen display	
Multi-language display	UK English, U
	Englis Simplifie
	Chinese, Françai Españo
Soft close doors	
True convection oven	
Turned stainless steel dials with illuminated halos	
Wireless temperature sensor compatible	

# Functions Air fry Bake Classic bake Dehydrate Fan bake Fan forced Fan grill Grill Number of functions Pastry Bake

Rapid proof      Roast      Slow cook      Vent bake      Warm      Performance      ActiveVent™ system      AeroTech™ technology      Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    Market and	Pyrolytic self-clean	•
Slow cook    Yent bake      Vent bake    Warm      Warm    Performance      ActiveVent™ system    AeroTech™ technology      AeroTech™ technology    Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    Market and	Rapid proof	
Vent bake    Warm      Warm    Performance      Active Vent™ system    AeroTech™ technology      AeroTech™ technology    Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    Output      Power requirements    Output      Amperage    15 A      Supply frequency    50 H2      Supply voltage    220-240 V      Product dimensions    Depth      Depth    565 mm      Height    598 mm	Roast	•
Warm    Performance      ActiveVent™ system    AeroTech™ technology      AeroTech™ technology    Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    Market and a start	Slow cook	•
Performance      ActiveVent™ system      AeroTech™ technology      Automatic rapid pre-heat      Grill power      Temperature range      35°C - 280°C      Whisper quiet cooking      Power requirements      Amperage      Supply frequency      Supply frequency      Supply voltage      Product dimensions      Depth    565 mm      Height    598 mm	Vent bake	•
ActiveVent™ system    AeroTech™ technology      Automatic rapid pre-heat    3000 W      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    0      Power requirements    15 A      Amperage    15 A      Supply frequency    50 H2      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	Warm	•
ActiveVent™ system      AeroTech™ technology      Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    0      Power requirements    0      Anted current    15 A      Supply frequency    50 H2      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm		
Aero Tech™ technology      Automatic rapid pre-heat      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    0      Power requirements    0      Amperage    15 A      Rated current    15 A      Supply frequency    50 Hz      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	Performance	
Automatic rapid pre-heat    3000 W      Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    9      Power requirements    9      Amperage    15 A      Rated current    15 A      Supply frequency    50 Hz      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	ActiveVent™ system	•
Grill power    3000 W      Temperature range    35°C - 280°C      Whisper quiet cooking    -      Power requirements    -      Amperage    15 A      Rated current    15 A      Supply frequency    50 Hz      Supply voltage    220-240 V      Product dimensions    -      Depth    565 mm      Height    598 mm	AeroTech™ technology	•
Temperature range    35°C - 280°C      Whisper quiet cooking    1      Power requirements    15 A      Amperage    15 A      Rated current    15 A      Supply frequency    50 Hz      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	Automatic rapid pre-heat	•
Whisper quiet cooking      Power requirements      Amperage    15 A      Rated current    15 A      Supply frequency    50 Hz      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	Grill power	3000 W
Power requirements      Amperage    15 A      Rated current    15 A      Supply frequency    50 H2      Supply voltage    220-240 V      Product dimensions    565 mm      Depth    565 mm      Height    598 mm	Temperature range	35°C - 280°C
Amperage  15 A    Rated current  15 A    Supply frequency  50 H:    Supply voltage  220-240 V    Product dimensions  565 mm    Depth  565 mm    Height  598 mm	Whisper quiet cooking	•
Rated current  15 A    Supply frequency  50 Hz    Supply voltage  220-240 V    Product dimensions  2000000000000000000000000000000000000	Power requirements	
Supply frequency  50 Hz    Supply voltage  220-240 V    Product dimensions  2000000000000000000000000000000000000	Amperage	15 A
Supply voltage 220-240 V Product dimensions Depth 565 mm Height 598 mm	Rated current	15 A
Product dimensions Depth 565 mm Height 598 mm	Supply frequency	50 Hz
Depth 565 mm Height 598 mm	Supply voltage	220-240 V
Height 598 mm	Product dimensions	
Height 598 mm	Depth	565 mm
		598 mm
		596 mm
	Safety	

Pizza bake

٠

•

#### QUICK REFERENCE GUIDE > OB60SD16PLX1

Balanced oven door	•
Catalytic venting system	•
Control panel key lock	•
CoolTouch door	•
Non-tip shelves	•
Safety thermostat	•

Warranty

Parts and labour	1 year
SKU	82554

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

#### Other product downloads available at fisherpaykel.com

- ↓ 2D-DWG Oven
- ↓ 2D-DXF Oven
- ▲ ArchiCAD Oven
- 🚽 🛛 Datasheet Oven
- Service & Warranty
- Installation Guide Wall Oven EN
- Installation Guide Wall Oven ZH
- 🕹 🛛 Revit Oven

 $\overline{\mathbf{1}}$ 

 $\overline{\uparrow}$ 

👃 🛛 Rhino Oven

- ✓ SketchUp Oven
  ✓ User Guide Oven EN
  ✓ XXXX ZH
- Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.