

# Wall Rangehood, 90cm, Box Chimney, with External Motor

Series 7 | Contemporary

Stainless Steel and Glass



This wall chimney rangehood has an externally installed inline motor to deliver near silent yet powerful extraction of steam, grease and cooking odours.

- External motor delivers near silent operation in the kitchen
- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful 1200m<sup>3</sup>/h maximum airflow
- Dimmable LED lighting illuminates the cooking surface beautifully

## DIMENSIONS

Height	595-1035 mm
Width	898 mm
Depth	500 mm

## FEATURES & BENEFITS

### Near Silent Extraction

The powerful external motor is installed outside the home to deliver near silent extraction of cooking odours and steam from the kitchen.

### Seamless Integration

Designed to match our Contemporary style appliances, this wall chimney rangehood features sleek black glass and stainless steel styling to complement any kitchen design.

### Effective Extraction

This rangehood features three fan speeds plus boost function, providing powerful extraction to quickly remove odours and steam. As odours can linger in the kitchen well after cooking is finished, the timer keeps the rangehood working for up to 15 minutes before automatically turning off.

### Full Surface Lighting

Low energy, dimmable LED lights provide superb illumination over the entire cooking surface.

### Easy To Use

This Fisher & Paykel rangehood features a sleek and easy to use touch-control panel.

### Easy Cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe. The stainless steel mesh cover just needs a quick wipe to keep clean. An alert reminds you when to clean the filter to ensure you get the best performance out of your rangehood.

### Considered Efficiency

The four speeds with a range of different airflows means you can effectively remove cooking odours with reduced effect on your heating or air conditioning, ensuring less energy is used.

## SPECIFICATIONS

### Accessories (included)

Aluminium filter	792577
External motor kit	50170 HB1200E* (included)

### Accessories (sold separately)

Chimney extension	792492
Extra ducting length	792961
Light bulb	792556

### Fan ratings

Maximum air movement	1200 m <sup>3</sup> /hr
Speed 1 sound rating	39 dBA

### Installation and cleaning

Air outlet size	200 mm
Dishwasher safe filters	3

Ducted	<b>Top extraction</b>
Stainless steel filter cover	•
Two piece height adjustable flue	•

Filter cleaning alert	•
Light type	<b>LED</b>
Timer function	•

### Performance

Extraction type	<b>Surface</b>
Fan speeds	<b>3</b>
Fan speeds + boost	•
Filter type	<b>Mesh</b>
Number of filters	<b>3</b>

### Warranty

Parts and labour	<b>2 years</b>
------------------	----------------

SKU	50169
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

### Other product downloads available at fisherpaykel.com

- [↓ Archicad Wall Rangehood](#)
- [↓ Service & Warranty](#)
- [↓ Installation Guide Rangehood External Blower](#)
- [↓ Installation Guide Integrated Insert Rangehood with External Blower](#)
- [↓ Revit Wall Rangehood](#)
- [↓ Rhino Wall Rangehood](#)
- [↓ Sketchup Wall Rangehood](#)
- [↓ User Guide Integrated Insert Rangehood with External Blower](#)
- [↓ User & Installation Guide Wall Rangehood Box Chimney with External Blower](#)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



**A PEACE OF MIND SALE**  
24 Hours 7 Days a Week Customer Support

T 0800 372 273 W [www.fisherpaykel.com](http://www.fisherpaykel.com)

### Power requirements

Lighting power	<b>8 W</b>
Supply frequency	<b>50 Hz</b>
Supply voltage	<b>220-240 V</b>

### Product dimensions

Depth	<b>500 mm</b>
Height	<b>595-1035 mm</b>
Width	<b>898 mm</b>

### Product information

Control type	<b>Capacitive touch</b>
--------------	-------------------------

### Ventilation features

Dimmable lights	•
-----------------	---