Gas Range 48", 6 Burners with Griddle, LPG

Series 7 | Professional

Stainless Steel | LPG



A striking addition to your kitchen, with six powerful gas burners and two gas ovens giving you a combined capacity of 7.7 cu ft.


- · Top burner heat of 19,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

DIMENSIONS

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "



FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Instant Visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Easy To Clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has been carefully crafted in every detail from performance to durability using quality materials.

SPECIFICATIONS

Accessories (sold separately)

Square handle option AH-R48

Burner ratings

Maximum burner power	19000 BTU
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	19000BTU
Power front right	15000BTU
Power griddle	15000BTU
Total cooktop power	103000 BTU

Capacity		Auto re-ignition system	•	Safety	
Shelf positions (main oven)	5	Internal light	true	ADA compliant	•
Shelf positions (second oven)	5			Full extension telescopic sliding shelves	•
		Power Requirements			
Controls		Amperage	15 A	Secondary oven features	
Electric circuit	3 wire	Rated current	15 A	3/4 Extension racks	2
Metal illuminated dials	•	Supply frequency	60 Hz	Electronic oven control	•
				Internal light	•
Gas Requirements		Product Dimensions			
Fitting and pipe	½ NPT, min. %″ 🛚	Depth	29 1/8 "	Secondary oven functions	
Titting and pipe	flex line	Depth (excluding handles)	29 1/8 "	Bake	
Supply Pressure (LPG)	11" to 14" W.C	Height	35 3/4 - 36 3/4 "	Number of secondary oven functions	2
		Width	47 7/8 "	Proof	•
Main oven features					
Broil pan	•	Rangetop features			
Electronic oven control	•	Sealed range top	•	SKU	71347
Full extension telescopic racks	•	Vent trim included	•		
Infrared broiler	•			The product dimensions and specifications in this page apply to the	snecific
Internal light	•			product and model. Under our policy of continuous improvement, t	hese
		Recommended Back Guards Ventilation		dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel	
Main and founding		Combustible situation	BGRV2-3048H		
Main oven functions		Minimum CFM	1200	Appliances Ltd 2020	
Bake	•	Non combustible situation	BGRV2-3048 / BGRV2-1248		
Broil	•	Decempended head		Other product downloads available at fisherpaykel.com	
Convection bake	•	Recommended hood	HCB48-12_N (48""	•	
Number of oven functions	3		Professional Range Hood,	<u>↓</u> 2D-DWG Gas Range	
			Dual Blower)	± 2D-DXF Gas Range	
Oven features				Data Sheet Gas Range	
Oven features					



Service & Warranty



Installation Guide EN / Guide d'installation FR



Planning Guide Gas Range

↓ User Guide EN

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com