QUICK REFERENCE GUIDE > HT90GHB2

90cm Series 7 Tilt Chimney Wall Cooker Hood

Series 7 | Contemporary

Stainless Steel and Glass




With a tilted black glass hood, this ventilation option saves on space while adding contemporary design to your kitchen.

- With four fan speeds, plus boost function, select the perfect extraction rate for your cooking
- Powerful maximum air movement 617m³/hr
- · Dishwasher safe filters that are easy to remove and clean

DIMENSIONS





FEATURES & BENEFITS

Effective And Quiet

This cooker hood features four fan speeds, plus a boost function, providing powerful extraction to quickly remove odours and steam. As odours can linger in the kitchen well after cooking is finished, the timer keeps the rangehood working for up to 15 minutes before automatically turning off.

Simple To Use

This Fisher & Paykel tilt cooker hood features a sleek and easy to use touch-control panel. Low energy, dimmable LED lights provide superb illumination over the entire cooking surface.

Easy Cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe. The black glass finish just needs a quick wipe to keep clean. An alert reminds you when to clean the filter to ensure you get the best performance out of your cooker hood.

Designed To Match

This wall chimney tilt cooker hood features sleek black glass and stainless steel styling which will complement any contemporary kitchen and is designed to match the rest of Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (included)

Aluminium filter 791761

Accessories (sold separately)

Eave ducting kit

PD-RHK15OE

Light bulb

792556

Recirculation diverter

791820

Roof ducting kit

PD-RHK15OR

Side wall ducting kit

PD-RHK15OW

Consumption

Energy rating B
Energy usage 47kWh/year
In-use energy carbon emissions estimate 14.5kgCO2e/year

Fan ratings

QUICK REFERENCE GUIDE > HT90GHB2

Maximum air movement	617 m³/hr	
Maximum pressured air movement EN61591 at boost	617 m³/hr	
Maximum sound rating	69 dB	
Installation and cleaning		
Air outlet size	150 mm	
Dishwasher safe filters	1	
Ducted	Top and back extraction	
Recirculation	Optional - top extraction	
Two piece height adjustable flue	•	
Performance		
Extraction type	Perimeter	
Fan speeds	4	
Filter type	Mesh with perimeter extraction	
Number of filters	1	
Power requirements		
Lighting power	7 W	
Motor power	130 W	
Rated current	3 A	
Nated carrent		
Supply frequency	50 Hz	
	50 Hz 220-240 V	

380 mm	
800-1140 mm	
900 mm	
Capacitive touch	
•	
•	
LED	
•	

SKU	50124

Parts and labour

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Where applicable:

5 years

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

