QUICK REFERENCE GUIDE > HP60IDCHX3

Integrated Insert Rangehood, 60cm

Series 7 | Integrated

Stainless Steel and Glass



This efficient, stylish rangehood in black glass and stainless steel integrates seamlessly above your cooktop.

- With four fan speeds, select the perfect extraction rate for your cooking
- Powerful maximum air movement 780m³/hr
- Energy-efficient LED lighting illuminates the cooking surface beautifully
- · Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

Height 315 mm

Width 530 mm

Depth 280 mm

FEATURES & BENEFITS

Achieve The Invisible

The Integrated Insert Rangehood fits seamlessly behind your kitchen cabinetry, providing ventilation that is as discreet as it is powerful.

Effective Extraction

Four fan speeds including the powerful "boost" option ensure that odours, vapour and steam are removed quickly and effectively.

Easy Cleaning

The glass and stainless steel finishes are easily wiped clean and the aluminium filters are dishwasher safe. An alert reminds you when to clean the filter so that you get the best possible performance.

Quality Materials

This rangehood comes in a sleek black glass finish with real stainless steel frame. Hidden energy-effcient LED strip lighting illuminates the cooking surface beautifully.

SPECIFICATIONS

Accessories (included)

Aluminium filter 792942

Accessories (sold separately)

Eave ducting kit

PD-RHK150E

Light bulb

requires service
to replace

Recirculation carbon filter

Recirculation diverter

Roof ducting kit

PD-RHK150T

Side wall ducting kit

PD-RHK150W

Fan ratings

Maximum air movement 780 m³/hr

Maximum pressured air movement EN61591 820 m³/hr
at boost

Maximum sound rating 65 dBA

Installation and cleaning

Air outlet size 150 & 120 mm

Dishwasher safe filters 2

Ducted Top extraction

Recirculation Optional - top extraction

Performance

Extraction type Perimeter
Fan speeds 4
Number of filters 2

Power requirements

QUICK REFERENCE GUIDE > HP60IDCHX3

Supply voltage	240 V
Product dimensions	
Depth	280 mm
Height	315 mm
Width	530 mm
Product information	
Control type	Capacitive touch
Ventilation features	
Dimmable lights	•
Filter cleaning alert	•
Light type	LED strip
Timer function	•
Warranty	
Parts and labour	2 years

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

SKU

Other product downloads available at fisherpaykel.com

Archicad Integrated Insert Rangehood

Service & Warranty

, Installation Guide

Installation Guide

Revit Integrated Insert Rangehood

Rhino Integrated Insert Rangehood

Sketchup Integrated Insert Rangehood

↓ User Guide - Integrated

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



50150

A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1300 650 590 Wwww.fisherpaykel.com