QUICK REFERENCE GUIDE > WB60SDEX2

60cm Series 9 Contemporary Warming Drawer

Series 9 | Contemporary

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Contemporary styling.

- A companion product, designed to match with other Contemporary style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- · Easy to clean smooth-glass base

 Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	140 mm
Width	596 mm
Depth	567 mm

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Capacity	
Cappuccino cups	20
Espresso cups	42
Maximum allowable weight	25 kg
Place settings	6
Usable depth	408 mm
Usable height	98 mm
Usable width	535 mm
Cleaning	
Easy clean smooth-glass base	•

Controls

Audio feedback	•
Automatic pre-set temp	peratures •
Automatic timers	30′, 45′, 1h, 2h, 4h, 6h
Delayed start	•
Electronic capacitive to	uch controls •
On/Off indicator	•
Pre-set heating function	ns •
Push-to-open drawer	•
Standby mode	•

QUICK REFERENCE GUIDE > WB60SDEX2 Date: 17.10.2024 > 2

Safety

Parts and labour

unctions		
Cups		
Dehydrate		
Number of functions		
Plates		
Rapid proof		
Slow cook		
Warm		
Performance		
Heated glass base and fan		
Low temperature cooking		
Temperature levels		
Temperature range	35°C-85°	
Power requirements Amperage	10 /	
Power cord length	1800 mr	
Power outlet	3-pron	
	grounding-typ	
Supply frequency	50 H	
Supply voltage	220	
Product dimensions		
Product dimensions Adjustable front door panel to align with surrounding cabinetry		
Adjustable front door panel to align with	567 mr	
Adjustable front door panel to align with surrounding cabinetry	567 mr 140 mr	

Salety	
Automatic turn off after 12 hours	•
Full extension slides	•
Warranty	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

_	
\underline{ullet}	2D-DXF Warming Drawer
$\underline{\downarrow}$	Archicad Warming Drawer
$\overline{\underline{\downarrow}}$	Service & Warranty
$\overline{\downarrow}$	Installation Guide
$\underline{\downarrow}$	Revit Warming Drawer
\underline{ullet}	Rhino Warming Drawer
$\overline{\underline{\downarrow}}$	Sketchup Warming Drawer
$\overline{\downarrow}$	User Guide Warming Drawer
$\overline{\bot}$	User Guide

2D-DWG Warming Drawer

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



2 years

A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com

Where applicable: