QUICK REFERENCE GUIDE > RGV3-304-L Date: 08.10.2024 > 1

30" Series 7 Professional 4 Burner Gas Range, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- · Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- · Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	29 7/8 "
Depth	29 1/8 "

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners[™] deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

Easy To Clean

With a continuous, porcelain basepan, cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories (sold separately)	
Square handle option	AH-R30
Wok grate included	Yes
Burner ratings	

Maximum burner power	17000 BTU
Power back left	13000BTU
Power back right	13000BTU
Power front left	17000BTU
Power front right	15000BTU
Total cooktop power	58000 BTU

Capacity

Shelf positions	5
Total capacity	4.6 cu ft
Usable capacity	3.4 cu ft

Cleaning

Easy clean porcelain basepan

Controls

Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

QUICK REFERENCE GUIDE > RGV3-304-L

Date: 08.10.2024 > 2

Fitting and pipe	½ NPT, min. %″ ∑ flex line		
Supply Pressure (LPG)	11" to 14" W.C		
Oven features			
Auto re-ignition system	•		
Broil pan	•		
Electronic oven control	•		
Full extension telescopic sliding shelves	•		
Infrared Broiler	•		
Internal light	true		
Titanium coated, illuminated metal dials	•		
Oven functions			
Bake	•		
Broil	•		
Convection bake	•		
Number of functions	4		
Slow cook	•		
Oven performance			
Bake power	21500		
Power requirements			
Service	15 A		
Supply	120 V, 60 Hz		

Product dimensions

Depth	29 1/8 "
Depth (excluding handles)	2918 mm
Height	35 3/4 - 36 3/4 "
Width	29 7/8 "

Rangetop features

Sealed range top		
Vent trim included		

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional Range Hood)

Safety

ADA compliant	•
Full extension telescopic sliding shelves	•

SKU		82005

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

$\underline{\downarrow}$	2D-DWG Gas Cooker
$\underline{\downarrow}$	2D-DXF Range
$\underline{\downarrow}$	ArchiCAD Gas Range
$\underline{\downarrow}$	Service & Warranty
$\underline{\downarrow}$	Revit Gas Range
$\underline{\downarrow}$	Rhino Gas Range
$\underline{\downarrow}$	Sketchup Gas Range
$\underline{\downarrow}$	Guide d'utilisation FR
$\underline{\downarrow}$	User Guide EN

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > RGV3-304-L Date: 08.10.2024 > 3

