Dual Fuel Range, 48", 6 Burners with Griddle

Series 9 Professional

Stainless Steel | Natural Gas



With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Gas cooktop with griddle and a top burner heat up to 23,500 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities
- Use the food probe to monitor your cooking real time

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 "

FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 23,500 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories (included)	
Adjustable feet covers	•
Branded coin end cap	•
Telescopic sliding runners	true

Accessories (sold separately)

Square handle option	AH-R48

Burner ratings

Maximum burner power	23500 BTU
Power back centre	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front left	23500BTU
Power front right	18500BTU
Power griddle	18000BTU
Total cooktop power	134000 BTU

QUICK REFERENCE GUIDE > RDV3-486GD-N

Capacity

Shelf positions (main oven)	5
Shelf positions (second oven)	5
Total capacity (main oven)	4.8 cu ft
Total capacity second oven	2.1 cu ft
Usable capacity (main oven)	3.8 cu ft

Cleaning

Easy clean porcelain basepan
Pyrolytic proof shelf runners

Controls

Dial with illuminated halo
Dual control oven dials
High resolution display
Multi-language interface
Precise cooking with food probe
recipeAndFoodBasedFunctions
Sabbath mode
Smart appliance
Tilting touch screen interface
Wi-Fi connectivity

Gas Requirements

Fitting and pipe	½ NPT, min. ⁵೫″ 🕅 flex line
Supply Pressure (natural gas)	6" to 9" W.C

Main oven features

Concealed Element
Electronic oven control
Food probe
Full extension telescopic racks
Internal light
Large broil pan
Self-clean proof side racks
True convection

Main oven functions

Air fry
Bake
Classic bake
Clean
Convection broil
Maxi broil
Number of oven functions
Pizza bake
Rapid proof
Roast
Slow cook
True convection
Warm

Oven features

Auto re-ignition system
Concealed element
Electronic oven control

Food probe • Full extension telescopic sliding shelves . Internal light true Large broil pan Self-clean proof side racks True convection

Oven functions

. 15

Air fry	•
Bake	•
Classic bake	•
Clean	•
Convection bake	•
Convection Broil	•
Dehydrate	•
Dehydrate	•
Maxi Broil	•
Number of functions	15
Pastry bake	•
Pizza bake	•
Rapid proof	•
Roast	•
Slow cook	•
True convection	•
Warm	•

Power Requirements

Connection	4-prong
	grounding type
	[NEMA 14-50P
	plug]

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RDV3-486GD-N

Service	50 A
Supply	120 / 240 V, 60 Hz
Product Dimensions	
Depth	29 1/8 "
Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Rangetop features	
Sealed range top	•
Vent trim included	•
Rangetop Performance	
Number of burners	6
Recommended Back Guards Ventilat	tion
Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48" Professional Range Hood, Dual Blower)
Safety	
ADA compliant	•
Child lock	•

Secondary oven features	
3/4 Extension racks	
Concealed element	
Electronic oven control	
Food probe	
Internal light	

Secondary oven functions		
Air fry	•	
Bake	•	
Classic bake	•	
Convection bake	•	
Convection broil	•	
Maxi broil	•	
Number of secondary oven functions	11	
Pastry bake	•	
Pizza bake	•	
Rapid proof	•	
Roast	•	
Warm	•	
Warranty		
Parts and labor	Limited 2 years	

Limited 2 years

SKU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

$\overline{1}$	2D-DWG Dual Fuel Range
$\overline{1}$	2D-DXF Dual Fuel Range
$\overline{1}$	ArchiCAD Dual Fuel Range
$\overline{1}$	Data Sheet Professional Range
$\overline{1}$	Service & Warranty
$\overline{1}$	Planning Guide Professional Style Dial/Handle Accessories
$\overline{\mathbf{h}}$	Revit Dual Fuel Range
$\overline{1}$	Rhino Dual Fuel Range
$\overline{1}$	SketchUp Dual Fuel Range
$\overline{1}$	User Guide EN
_	

Where applicable:

2

82385

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com