

48" Series 9 5 Burner with Griddle Gas Rangetop, LPG

Series 9 | Professional

Stainless Steel | LPG



A powerful five burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Your burners can deliver anything from very high 19,000 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from pancakes to bacon, grilled cheese to quesadillas

- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16 "
Width	47 7/8 "
Depth	28 "

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design Quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

SPECIFICATIONS

Burner ratings

Maximum burner power	Yes
Power back left	11,500 BTU
Power back right	11,500 BTU
Power front centre	19,000 BTU
Power front left	15,000 BTU
Power front right	15,000 BTU
Power griddle	24,000 BTU
Total cooktop power	96,000 BTU

Cleaning

- Easy clean porcelain basepan

Controls

- Metal illuminated dials
- Star K Certification
- Titanium coated, illuminated metal dials

Gas Requirements

Fitting and pipe	½ NPT, min. ⅝" flex line
Supply Pressure (LPG)	11" to 14" W.C

Performance

Sealed cooking surface	•
Sealed Dual Flow Burners™	5
Sealed range top	•
Simmer on all burners	140 °F

Power Requirements

Amperage	15 A
Supply frequency	60 Hz
Supply voltage	120 V

Product Dimensions

Depth	28 "
Height	8 5/16 "
Width	47 7/8 "

Recommended Back Guards Ventilation

Combustible situation	BGCV2-3048H
Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N

Safety

ADA compliant	•
---------------	---

Zone ratings

Front right **18500 BTU**

SKU 82011

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓ 2D-DWG Gas Rangetop](#)
- [↓ 2D-DWG Gas Rangetop and Low Backguard](#)
- [↓ 2D-DWG Gas Rangetop and Low Shelf High Backguard](#)
- [↓ 2D-DWG Gas Rangetop and High Shelf High Backguard](#)
- [↓ 2D-DXF Gas Rangetop](#)
- [↓ 2D-DXF Gas Rangetop and Low Backguard](#)
- [↓ 2D-DXF Gas Rangetop and Low Shelf High Backguard](#)
- [↓ 2D-DXF Gas Rangetop and High Shelf High Backguard](#)
- [↓ ArchiCAD Gas Rangetop](#)
- [↓ Data Sheet Gas Rangetop](#)
- [↓ Data Sheet Gas Rangetop and Low Backguard](#)
- [↓ Data Sheet Gas Rangetop and Low Shelf High Backguard](#)
- [↓ Data Sheet Gas Rangetop and High Shelf High Backguard](#)
- [↓ Service & Warranty](#)
- [↓ Installation Guide EN](#)
- [↓ Planning Guide Professional Style Dial/Handle Accessories](#)
- [↓ Revit Gas Rangetop](#)
- [↓ Rhino Gas Rangetop](#)
- [↓ SketchUp Gas Rangetop](#)

[↓ User Guide](#)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
 24 Hours 7 Days a Week Customer Support
 T 1.888.936.7872 Wwww.fisherpaykel.com