QUICK REFERENCE GUIDE > CPV3-486GD-L Date: 09.07.2024 > 1

Gas Rangetop, 48", Griddle, LPG

Series 9 | Professional

Stainless Steel | LPG



A powerful six burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Griddle with burners that deliver up to 19,000 BTU heat per burner, for seriously fast boiling
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from grilled cheese to quesadillas

Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16 "
Width	47 7/8 "
Depth	28 "

FEATURES & BENEFITS

Cooktop Power

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy To Clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design Quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron trivets, and titanium coated dials.

SPECIFICATIONS

Burner ratings	
Maximum burner power	Yes
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	19000BTU
Power front right	15000BTU
Power griddle	15000BTU
Total cooktop power	103000BTU
Number of burners	6
Cleaning	
Easy clean porcelain basepan	•
Controls	
Metal illuminated dials	•
Star K Certification	•

Gas Requirements

QUICK REFERENCE GUIDE > CPV3-486GD-L Date: 09.07.2024 > 2

Fitting and pipe	½ NPT, min. 5%" ☐ flex line
Supply Pressure (LPG)	11" to 14" W.C
Performance	
Auto re-ignition system	•
Sealed Dual Flow Burners™	6
Sealed range top	•
Simmer on all burners	140 °F
Power requirements	
Supply frequency	60 Hz
Supply voltage	120 V
Product dimensions	
Depth	28 "
Depth Height	28 " 8 5/16 "
Height	8 5/16 "
Height Width	8 5/16 "
Height Width Recommended Back Guards Ventilation	8 5/16 " 47 7/8 "
Height Width Recommended Back Guards Ventilation Combustible situation	8 5/16 " 47 7/8 " BGCV2-3048H BGCV2-3048 /
Height Width Recommended Back Guards Ventilation Combustible situation Non combustible situation	8 5/16 " 47 7/8 " BGCV2-3048H BGCV2-3048 / BGCV2-1248

Zones

Number of zones 6

SKU 82388

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

Energy Label

Service & Warranty

Installation Guide EN

. Guide d'installation FR

Planning Guide Professional Style Dial/Handle Accessories

Revit Gas Rangetop

Rhino Gas Rangetop

, SketchUp Gas Rangetop

User Guide EN

Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com