QUICK REFERENCE GUIDE > OR90SCG2X1

90cm Series 7 Classic 5 Burner Dual Fuel Cooker

Series 7 | Classic

Stainless Steel



Get the best of both worlds with dual fuel. A gas cooktop with wok burner is paired with a nine-function convection oven.


- · Five burner gas cooktop, with precise heat control
- Convection oven with 140L total capacity and nine oven functions including Pastry Bake and Rapid Proof
- · Non-tip full-extension shelves for safe removal of hot dishes

DIMENSIONS

 Height
 898 - 946 mm

 Width
 897 mm

 Depth
 600 mm



FEATURES & BENEFITS

Multi-Shelf Cooking

Our AeroTech™ system circulates air evenly throughout the entire oven so dishes on the top shelf turn out just as perfectly as food cooking on the bottom shelf.

Quality And Durability

Every detail has been carefully crafted. The solid, perfectly balanced soft-close door and durable cooktop trivets all add up to an exceptional, premium range.

Burner Power & Control

Instant and immediate control from the highest to the gentlest heat. The finely tuned cooktop controls let you sear, stir fry or simmer a delicate sauce to perfection.

Large Capacity Oven

The generous 140L total capacity oven gives you plenty of space to cook multiple dishes at once.

Easy To Clean

Your cooktop simply needs a quick wipe to keep it looking good as new for years to come, as the gas cooktop is made from a single piece of stainless steel that contains spills. The oven door, its inner pane of glass and runners can also be removed for easy cleaning.

Even Heat

Accurate, electronically-controlled oven heat ensures a great result every time.

SPECIFICATIONS

Accessories (included)

Chromed shelf runners	1 set
Flat wire shelf	1
Roasting dish	1
Small pot support	1 (part 533981 cast)
Step down wire shelf	

Accessories (sold separately)

Full extension sliding shelves	Optional (part 578744)
Full extension telescopic shelves	Optional (part 578744)
Kick strip, stainless steel (optional)	KICKOR90X1

QUICK REFERENCE GUIDE > OR90SCG2X1 Date: 24.09.2024 > 2

Shelf positions Shelf positions (main oven) Shelf positions (main oven) Shelf positions (main oven) Shelf positions (main oven) Total capacity 140 L Usable capacity Usable capacity Usable capacity (main oven) 121 L Electronic oven control Controls Electronic oven control Electr	Burner ratings		Celsius/Fahrenheit temperature	•	Fan grill	•
Maximum burner power 16.2ML/h Procise electronic temperature control Pastry Bake with Pizza mode Pastry Bake with Pi	Dual wok burner inner/outer (LPG)	14.9MJ/h	Electronic clock	•	Grill	•
Semi-rapid burner (natural gas) SaMu/h Sabbath mode Rapid proof Samu/h Semi-rapid burner (natural gas) x2 6.5 Mu/h Turned stainless steel clock buttons Rapid proof Rosat Turconvection	Dual wok burner inner/outer (natural gas)	16.2MJ/h	Laser etched graphics	•	Number of functions	9
Semi-rapid burner (natural gas) 2 6.5MJ/h Total cooktop power 58.0MJ/h Total cooktop power 61.0MJ/h Total cooktop power 61.0MJ/h Sheft positions 66 6	Maximum burner power	16.2MJ/h	Precise electronic temperature control	•	Pastry Bake with Pizza mode	•
Triple ring wok burner (LPG) x2	Semi-rapid burner (natural gas)	5.8MJ/h	Sabbath mode	•	Rapid proof	•
Triple ring wok burner (LPG) x2 14.4MJ/h Triple ring wok burner (natural gas) x2 14.4M	Semi-rapid burner (natural gas) x2	6.5MJ/h	Turned stainless steel clock buttons	•	Roast	•
Tiple ring wok burner (natural gas) x2	Total cooktop power	58.0MJ/h			True convection	•
Triple ring work burner (natural gas) x2	Triple ring wok burner (LPG) x2	14.4MJ/h				
Capacity Shelf positions (Midh) 900 mm Shelf positions (Midh) 900	Triple ring wok burner (natural gas) x2	14.4MJ/h	Installation Dimensions			
Shelf positions Shelf positions (main oven) Shelf position			Installation cutout dimensions (Depth)	600 mm	Oven performance	
Shelf positions Shelf positions (main oven) Shelf positions (main oven) Shelf positions (main oven) Shelf positions (main oven) Total capacity 140 L Usable capacity Usable capacity Usable capacity (main oven) 121 L Electronic oven control Controls Electronic oven control Electr			Installation cutout dimensions (Width)	900 mm	CoolTouch door	Triple glazed
Shelf positions (main oven) 6 Total capacity 140 L AeroTech™ technology Supply frequency 121 L Usable capacity (main oven) 121 L Usable capa	Capacity					
Shelf positions (main oven) 140 L AeroTech™ technology Amperage 22 A Usable capacity 121 L Usable capacity (main oven) 121 L Electronic oven control Electronic oven control Full extension telescopic sliding shelves Cleaning Cleaning Cleaning Cleaning Acid resistant graphite enamel Drop down grill element Removable oven door Removable oven door Removable oven door Removable shelf runners Removable shelf runners Controls Acid resistant Aduloi feedback Automatic cooking/minute timer Acid sessed a service of the ser	Shelf positions	6				
Usable capacity (main oven) 121 L Automatic rapid pre-heat	Shelf positions (main oven)	6	Oven reatures		Power requirements	
Usable capacity (main oven) 21 L Bright chromed, cast zinc dials with illuminated halos Supply voltage 220 - 240 V	Total capacity	140 L	AeroTech™ technology	•	Amperage	22 A
Cleaning	Usable capacity	121 L	Automatic rapid pre-heat	•	Supply frequency	50 Hz
Cleaning Acid resistant graphite enamel Acid resistant graphite Acid Resistant graph	Usable capacity (main oven)	121 L		•	Supply voltage	220 - 240 V
Acid resistant graphite enamel Acid resistant graphite enamel Prop down grill element Removable oven door Removable oven door inner glass Removable shelf runners Controls Audio feedback Automatic cooking/minute timer Acid resistant graphite enamel Internal light Ax 25W halogen (2 side & 2 top) Pepth Ax 25W halogen (2 side & 2 top) Pepth Acid resistant graphite enamel Ax 25W halogen (2 side & 2 top) Pepth Acid resistant Ax 25W halogen (2 side & 2 top) Pepth Acid Resistant graphite enamel Internal light Ax 25W halogen (2 side & 2 top) Pepth Acid resistant Acid resistant graphite enamel Internal light Ax 25W halogen (2 side & 2 top) Pepth Acid Resistant graphite enamel Internal light Ax 25W halogen (2 side & 2 top) Pepth Acid Resistant graphite enamel Internal light Ax 25W halogen (Acid Resistant graphite enamel Internal light Ax 25W halogen (Both Both Acid Sale Acid Resistant			Electronic oven control	•		
Acid resistant graphite enamel Porp down grill element Removable oven door Removable oven door inner glass Removable shelf runners Controls Audio feedback Automatic cooking/minute timer Acid resistant graphite enamel Internal light 4 x 25W halogen (2 side & 2 top) Bepth 4 x 25W halogen (2 side & 2 top) Depth 600 mm 4 width 898 - 946 mm Width 898 - 946 mm Width 897 mm Width 897 mm Removable oven door inner glass Fangetop features Rangetop features Hob rail Controls Automatic cooking/minute timer Fangetop features Controls Automatic cooking/minute timer Fangetop features Automatic solicy and solicy a	Cleaning		Full extension telescopic sliding shelves	•	Product dimensions	
Removable oven door	-	•	Internal light		Depth	600 mm
Removable oven door inner glass Removable shelf runners Oven functions Bake Audio feedback Automatic cooking/minute timer Twin cavity fans Twin cavity fans Rangetop features Hob rail Oven functions Hob rear trim 60 mm LPG / Natural Gas compatible Pan bake Sealed range top	Drop down grill element	•	Storage compartment	•	Height	898 - 946 mm
Removable shelf runners Oven functions Hob rail Controls Audio feedback Automatic cooking/minute timer Rangetop features Hob rail LPG / Natural Gas compatible LPG / Natural Gas compatible Sealed range top	Removable oven door	•	True convection	•	Width	897 mm
Controls Hob rear trim 60 mm Audio feedback • Classic bake • LPG / Natural Gas compatible • Sealed range top Automatic cooking/minute timer • Fan bake • Sealed range top • Sealed range top	Removable oven door inner glass	•	Twin cavity fans	•		
Oven functions Hob rail • Controls Bake • Hob rear trim 60 mm Audio feedback • Classic bake • LPG / Natural Gas compatible • Automatic cooking/minute timer • Fan bake • Sealed range top •	Removable shelf runners	•			_	
Controls Bake Classic bake Classic bake Automatic cooking/minute timer Automatic cooking/minute timer Bake Classic bake Classic bake Fan bake Fan bake Sealed range top Sealed range top					Rangetop features	
Audio feedback Automatic cooking/minute timer • Classic bake • LPG / Natural Gas compatible • Sealed range top • Sealed range top			Oven functions		Hob rail	•
Automatic cooking/minute timer • Fan bake • Sealed range top	Controls		Bake	•	Hob rear trim	60 mm
Automatic cooking/minute timer	Audio feedback	•	Classic bake	•	LPG / Natural Gas compatible	•
Automatic pre-set temperatures • Fan forced •	Automatic cooking/minute timer	•	Fan bake	•	Sealed range top	•
	Automatic pre-set temperatures	•	Fan forced	•		

QUICK REFERENCE GUIDE > OR90SCG2X1

Rangetop Performance

Number of burners 5

Safety

Advanced cooling system

Anti-tilt bracket

Balanced oven door

CoolTouch door

Flame failure system

Full extension telescopic shelves Optional (part 578744)

Non-tip shelves

Spill containment 26 L

Warranty

Parts and labour 2 years

SKU 81680

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Service & Warranty

1

Installation Guide

 $\overline{\mathbf{4}}$

Installation Guide - Kick Strip



Revit Dual Fuel Cooker



Rhino Dual Fuel Cooker
Sketchup Dual Fuel Cooker



User Guide

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 0800 372 273 Wwww.fisherpaykel.com