60cm Series 3 Telescopic Wall Rangehood

Series 3 | Contemporary

White




The wall chimney rangehood has contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of $340 m^3/hr$
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

Height	181-185 mm
Width	598 mm
Depth	280-460 mm



FEATURES & BENEFITS

Easy Installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Easy To Use

Simply flick a switch to turn this rangehood on or off, or to change the extraction speed. A separate switch controls the bright halogen lights to provide illumination over your cooking surface.

Easy Cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless Integration

This rangehood can be built into your cabinetry for a seamless look. Its stainless steel finish is designed to match the rest of Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (included)

Aluminium filter

7	9	2	3	9	1
,	3	~	-	3	

Accessories (sold separately)

Eave ducting kit	PD-RHK125E
Light bulb	791822
Recirculation carbon filter	792390
Roof ducting kit	PD-RHK125T
Side wall ducting kit	PD-RHK125W

Fan ratings

Maximum air movement	340 m³/hr
Maximum sound rating	66 dBA

Installation and cleaning

Air outlet size	120 mm
Dishwasher safe filters	2

QUICK REFERENCE GUIDE > HS60XW4

Ducted	Top extraction only	SKU
Performance		The product d product and m
Extraction type	Surface	dimensions an check with Fis
Fan speeds	2	correctly desc Appliances Ltc
Filter type	Mesh	Appliances Ltc
Number of filters	2	
		Other produ
Power requirements		👃 Service
Supply frequency	50 Hz	↓ Service ↓ Installa ↓ User G
Supply voltage	220-240 V	↓ User G
Product dimensions		Where appli
Depth	280-460 mm	All appliance carbon emiss
Height	181-185 mm	Carbon Emis
Width	598 mm	product's in- cycle, using t
		consumptior energy in yo
Product information		Our In-use E
Control type	Switch	customers in comparing d
Ventilation features		pump dryer Estimate tha
1 in lake to one		\frown
Light type	LED	24/7
Warranty		
Parts and labour	2 years	

50016

dimensions and specifications in this page apply to the specific model. Under our policy of continuous improvement, these nd specifications may change at any time. You should therefore sher & Paykel's Customer Care Centre to ensure this page cribes the model currently available. © Fisher & Paykel td 2020

uct downloads available at fisherpaykel.com

- ce & Warranty
- ation Guide
- Guide

licable:

ces use energy, and energy usage typically generates ssions. Fisher & Paykel Appliances' In-use Energy issions Estimate indicates carbon emissions from a n-use energy. This is calculated either annually or per the product's market-specific energy label energy on data multiplied by the carbon emissions factor for our country or region.

Energy Carbon Emissions Estimate is designed to assist in making informed purchasing decisions when different Fisher & Paykel products. For example, a heat r typically has a lower In-use Energy Carbon Emissions an a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 0800 372 273 Wwww.fisherpaykel.com

FISHER & PAYKEL