QUICK REFERENCE GUIDE > RGV3-485GD-L Date: 04.07.2024 > 1

Gas Range, 48", 5 Burners with Griddle, LPG

Series 7 | Professional

Stainless Steel | LPG



With Professional styling, this large range has five burners delivering powerful high heat, a griddle and two gas ovens.

- Griddle with burners that deliver up to 17,000 BTU heat per burner, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- · Made from quality materials and real stainless steel

DIMENSIONS

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey. The griddle plate allows you to cook several foods at once.

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Burner ratings

Maximum burner power	16000 BTU
Power back left	11500BTU
Power back right	11500BTU
Power centre	16000BTU
Power front left	15000BTU
Power front right	15000BTU
Power griddle	22000BTU
Total cooktop power	91000 BTU

Capacity

Shelf positions (main oven)	5
Shelf positions (second oven)	5
Total capacity (main oven)	5.3 cu ft
Total capacity second oven	2.4 cu ft
Usable capacity (main oven)	3.9 cu ft

Cleaning

Easy clean porcelain basepan

Controls

Electric circuit

Metal illuminated dials

•

QUICK REFERENCE GUIDE > RGV3-485GD-L Date: 04.07.2024 > 2

Gas Requirements		Bake	•	Safety	
Fitting and pipe	½ NPT, min. 5%" 🛭	Broil •		ADA compliant •	
	flex line	Convection bake	•	Full extension telescopic sliding shelves	•
Supply Pressure (LPG)	11" to 14" W.C	Slow cook	•		
				Secondary oven features	
Main oven features		Power requirements		3/4 Extension racks	2
Electronic oven control	•	Amperage	15 A	Electronic oven control	•
Full extension telescopic racks	•	Supply frequency	60 Hz	Internal light	•
Infrared broiler	•				
Internal light	•				
		Product dimensions		Secondary oven functions	
		Depth	29 1/8 "	Bake	•
Main oven functions		Depth (excluding handles)	2918 mm	Convection bake	•
Bake	•	Height	35 3/4 - 36 3/4 "	Number of secondary oven functions	4
Broil	•	Width	47 7/8 "	Proof	•
Convection bake	•			Slow cook	•
Number of oven functions	4			Slow cook	
Slow cook	•	Rangetop features			
		Sealed range top	•		
Oven features		Vent trim included	•	SKU	81997
Auto re-ignition system	•			The product dimensions and specifications in this p	age apply to the specific
Electronic oven control	•	Recommended Back Guards Ventilation product and model. Under our policy of continuous impro dimensions and specifications may change at any time. You			
Full extension telescopic sliding shelves	•	Combustible situation	BGRV3-3048H	check with Fisher & Paykel's Customer Care Centre	
Infrared Broiler	•	Non combustible situation	BGRV2-3048 /	correctly describes the model currently available. ©	Fisher & Paykel
Internal light	true		BGRV2-1248	Appliances Ltd 2020	
Titanium coated, illuminated metal dials	•	Recommended hood	HCB48-12_N (48""		
			Professional Range Hood, Dual Blower)	Other product downloads available at fisher	rpaykel.com
Oven functions			Duai Biower)	↓ ArchiCAD Gas Range	
				ArchiCAD Gas Range	

QUICK REFERENCE GUIDE > RGV3-485GD-L

Date: 04.07.2024 > 3

 $\overline{\mathbf{\Lambda}}$

Service & Warranty

 \downarrow

Installation Guide

 $\overline{\mathbf{\Lambda}}$

Guide d'installation FR

 $\underline{\downarrow}$

Revit Gas Range

SketchUp Gas Range

 $\underline{\downarrow}$

User Guide

 \downarrow

Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com