
QUICK REFERENCE GUIDE > DD60SCTW9

Series 7, Contemporary Tall Single DishDrawer Dishwasher

Series 7 | Contemporary

White




Created with extra height for large dishes and designed to be placed anywhere in your kitchen, for loading dishes with less bending.

- With extra height for taller dishes, and customisable internal shelving
- Quick wash, Sanitise and Extra Dry options provide superior performance

DIMENSIONS

Height	454 mm
Width	599 mm
Depth	573 mm



FEATURES & BENEFITS

Quick, Sanitise and Extra Dry options

The Quick wash modifier delivers a faster wash while maintaining performance. The Sanitise option provides extra protection, killing 99.9% of bacteria in the final rinse. The Extra Dry setting is perfect for plastic dishes.

Quiet Performer

Running at a very low decibel rate, these DishDrawer™
Dishwashers do their job without making a fuss. The
combination of intelligent technology and simple mechanics
means greater reliability and excellent wash performance.

Seamless Integration

DishDrawer™ Dishwashers integrate beautifully into any kitchen space. They're designed to match the Fisher & Paykel family of kitchen appliances, with matching handles, premium styling and quality materials.

SPECIFICATIONS

Accessories (included)

Cutlery basket	•
Knife clip and multipurpose clip	•

Capacity and loading

Accommodates round plates up to	310mm
Adjustable height, foldable cupracks	•
Fold down tines	•
Pitch adjustable tines	•
Place settings	7

Consumption

3.5 star	Energy rating
136kWh/year	Energy usage
e 88.6kgCO2e/year	In-use energy carbon emissions estimate
6.9L	Water consumption (per wash cycle)
4.5 star (WELS)	Water rating

QUICK REFERENCE GUIDE > DD60SCTW9 Date: 18.10.2024 > 2

Electronic fault/Diagnostic indicator	Controls		Width	599 mm
Energy saving delay start option of up to 12 hours	Electronic fault/Diagnostic indicator	•		
Energy saving delay start option of up to 12 hours Parts and labour 2 years Keylock . . Rinse aid indicator light . Wash Program Modifiers Features Extra Dry Quick . Fan assisted drying . Sanitise . Flood protection . Wash modifiers 3 Flow through detergent dispenser . . Motor type BLDC Wash Programs Guilet operation . Wash Programs SmartDrive" technology . Delicate . Eco . . Fast . . Heavy . . Noise emissions 42 dBA Medium . Rinse . . Power requirements . . Supply frequency 50Hz Water connection Supply voltage 220 - 240V Water specture 30kPa - 1000 kPa Product dimensions . . . Bepth<	End of cycle beeps	•	Manusantus	
Rinse aid indicator light		•		2 years
Features Extra Dry • Fan assisted drying • Guick • Flood protection • Wash modifiers 3 Flow through detergent dispenser • Wash modifiers 3 Motor type BLDC ————————————————————————————————————	Keylock	•		
Features Features A Quick Quick A Sanitise A Sanitise A Wash modifiers BLDC Quiet operation A Wash Programs SmartDrive™ technology BLDC Performance Noise emissions Amperage Amperage Amperage Supply frequency Supply voltage Product dimensions Extra Dry Quick Quick A Quick A Quick A Quick A Sanitise A Wash modifiers A Wash modifiers A Wash modifiers A Wash modifiers A Wash Programs A Wash Programs BLDC A Wash Programs A Medium A Rinse Wash programs A Wash programs A Water connection Wash programs A Water supply	Rinse aid indicator light	•		
Features Quick • Fan assisted drying • Sanitise • Flood protection • Wash modifiers 3 Flow through detergent dispenser • Wash modifiers 3 Motor type BLDC **** ***** ***** ****** ****** ****** ******* ******* ******* *********** ************ *********************** ************************************			Wash Program Modifiers	
Fan assisted drying			Extra Dry	•
Flood protection	Features		Quick	•
Flow through detergent dispenser Motor type BLDC Quiet operation SmartDrive™ technology Performance Noise emissions August programs Power requirements Amperage Supply frequency Supply voltage Product dimensions Delicate Eco Fast Heavy	Fan assisted drying	•	Sanitise	•
Motor type Quiet operation SmartDrive" technology Delicate Eco Fast Heavy Noise emissions August and a series of the series of t	Flood protection	•	Wash modifiers	3
Quiet operation. Wash ProgramsSmartDrive™ technology. Delicate.PerformanceFast.Noise emissions42 dBAMedium.RinsePower requirements. Wash programs.Amperage. 5AWater connectionSupply frequency. 50HzWater pressure. 30kPa - 1000 kPaSupply voltage. 220 - 240VWater supply. 3/4" BSP (20mm) Connector Water Inlet HoseProduct dimensions. Water supply. 3/4" BSP (20mm) Connector Water Inlet HoseDepth. 573 mmHeight. 454 mm	Flow through detergent dispenser	•		
SmartDrive™ technology Delicate Eco Fast Heavy Noise emissions 42 dBA Nedium Rinse Wash programs 6 Power requirements Amperage Supply frequency Supply voltage Supply voltage Delicate Eco Fast Heavy Nedium Rinse Wash programs 6 Wash programs 6 Water connection Water repssure Water supply Water supply Water supply Supply voltage Product dimensions Depth Forduct dimensions Depth Forduct dimensions Depth Forduct dimensions Product dimensions Am Delicate Eco Water Fast Heavy Medium Noise Water connection Water connection Water pressure Water supply SokPa - 1000 kPa Afa''' BSP (20mm) Connector Water Inlet Hose	Motor type	BLDC		
Performance Noise emissions 42 dBA Medium Rinse Wash programs 6 Power requirements Amperage Supply frequency Supply voltage 220 - 240V Water connection Water connection Water supply Water supply Year	Quiet operation	•	Wash Programs	
Performance Noise emissions 42 dBA Nedium Rinse Wash programs 6 Power requirements Amperage Supply frequency Supply voltage Supply voltage Product dimensions Depth S73 mm Height Fast Heavy Medium Rinse Wash programs 6 Water connection Water connection Water pressure Water supply SokPa - 1000 kPa Water supply	SmartDrive™ technology	•	Delicate	•
Performance Noise emissions 42 dBA Medium Rinse Wash programs 6 Power requirements Amperage Supply frequency Supply voltage Supply voltage Product dimensions Depth Fight Figh			Eco	•
Noise emissions 42 dBA Medium Rinse Wash programs 6 Power requirements Amperage 5A Supply frequency Supply voltage 220 - 240V Product dimensions Depth Heavy Medium Water connection Water connection Water pressure Water supply Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Inlet Hose Heavy Medium Water programs Foundations Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Water supply April 1			Fast	•
Rinse Wash programs 6 Power requirements Amperage Supply frequency Supply voltage Supply voltage Product dimensions Depth Height Rinse Wash programs Water connection Water connection Water pressure Water supply Water supply J/4" BSP (20mm) Connector Water Inlet Hose	Performance		Heavy	•
Power requirements Amperage 5A Supply frequency 50Hz Water connection Supply voltage 220 - 240V Water pressure Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Product dimensions Depth 573 mm Height 454 mm	Noise emissions	42 dBA	Medium	•
Amperage 5A Supply frequency 50Hz Water connection Supply voltage 220 - 240V Water pressure 30kPa - 1000 kPa Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Product dimensions Depth 573 mm Height 454 mm			Rinse	•
Amperage 5A Supply frequency 50Hz Water connection Supply voltage 220 - 240V Water pressure 30kPa - 1000 kPa Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Product dimensions Depth 573 mm Height 454 mm			Wash programs	6
Supply frequency Supply voltage 220 - 240V Water pressure Water supply Water supply Froduct dimensions Depth Height Mater connection Water pressure Water supply Froduct dimensions Water supply Water supply S73 mm Height	Power requirements			
Supply voltage 220 - 240V Water pressure Water supply Water supply Water supply Tonnector Water Inlet Hose Product dimensions Depth Height 454 mm	Amperage	5A		
Water supply Water supply 3/4" BSP (20mm) Connector Water Inlet Hose Product dimensions Depth 573 mm Height 454 mm	Supply frequency	50Hz	Water connection	
Product dimensions Depth 573 mm Height 454 mm	Supply voltage	220 - 240V	Water pressure	30kPa - 1000 kPa
Product dimensions Depth 573 mm Height 454 mm			Water supply	Connector Water
Height 454 mm	Product dimensions			
	Depth	573 mm		
SKU 82317	Height	454 mm		
			SKU	82317

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

2D-DWG Single DishDrawer™ Dishwasher 2D-DXF Single DishDrawer™ Dishwasher Data Sheet Single DishDrawer™ Dishwasher Energy & Water Label DishDrawer™ Service & Warranty Installation Guide Single DishDrawer™ Dishwasher Revit Single DishDrawer™ Dishwasher Rhino Single DishDrawer™ Dishwasher Sketchup Single DishDrawer™ Dishwasher Specification Guide Single DishDrawer™ Dishwasher User Guide DishDrawer™ Dishwasher Wash Program Data ASNZS DishDrawer™ Dishwasher

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > DD60SCTW9

