48" Series 7 Professional 8 Burner Gas Range, LPG

Stainless Steel | LPG



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 ″

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

Cooktop Power

Sealed Dual Flow Burners[™] deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

17000 BTU
13000BTU
13000BTU
13000BTU
13000BTU
15000BTU
15000BTU
17000BTU
17000BTU
116000 BTU

Capacity

Shelf positions	5
Total capacity (main oven)	5.3 cu ft
Total capacity second oven	2.4 cu ft
Usable capacity (main oven)	3.9 cu ft

Cleaning

Easy clean porcelain basepan

Controls

Electric circuit

3 wire

QUICK REFERENCE GUIDE > RGV3-488L

Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %″ ሺ flex line
Supply Pressure (LPG)	11" to 14" W.C
Main oven features	
Broil pan	•
Electronic oven control	•
Full extension telescopic racks	•
Internal light	
Main oven functions	
Bake	•
Broil	•
Convection bake	•
Number of oven functions	4
Slow cook	•

Oven features

Auto re-ignition system
Electronic oven control
Full extension telescopic sliding shelves
Internal light
Titanium coated, illuminated metal dials

Oven functions

Bake		
Broil		
Convection bake		
Slow cook		

Power requirements

Service	15 A
Supply	120 V, 60 Hz

Product dimensions

Depth	29 1/8 "
Depth (excluding handles)	29 1/8 ″
Height	35 3/4 - 36 3/4 "
Width	47 7/8 "

Rangetop features

Sealed range top Vent trim included

true

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48" Professional Range Hood, Dual Blower)

Safety

٠

ADA compliant	
Full extension telescopic sliding shelves	
Secondary oven features	
3/4 Extension racks	
Electronic oven control	
Internal light	
Internal light	
Secondary oven functions	
Internal light Secondary oven functions Bake Convection bake	
Secondary oven functions	
Secondary oven functions Bake Convection bake	

SKU

81995

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

↓ ArchiCAD Gas Range

FISHER & PAYKEL

- ↓ Service & Warranty
- 🞍 🛛 Revit Gas Range
- 🞍 Rhino Gas Range
- ↓ Sketchup Gas Range
- ↓ User Guide
- ↓ Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 Wwww.fisherpaykel.com