48" Series 11 Professional 4 Burner + 4 Zone Hybrid Self-Cleaning Range, LPG

Series 11	Professional	

Stainless Steel | LPG




With both induction and gas cooktops and two convection ovens, you're ready to create a feast - guided by an intuitive touchscreen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 19,000 BTU, for seriously fast boiling
- Four induction cooking zones, which can be paired to form two SmartZones

• 6.9 cu ft total oven capacity across two oven cavities

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 ″



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

On the gas side of the cooktop, Sealed dual flow burners deliver power up to 19,000 BTU, while the induction side delivers up to 3700W. This finely tuned cooktop provides instant and immediate control from the highest heat to the most gentle simmer.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function. The induction zones only need a quick wipe after use to keep them clean.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers

QUICK REFERENCE GUIDE > RHV3-484-L

Branded coin end cap

Burner ratings

Maximum burner power	19000 BTU
Power back left	13000BTU
Power back right	13000BTU
Power front left	19000BTU
Power front right	13000BTU
Total cooktop power	58000 BTU

Capacity

5
5
4.8 cu ft
2.1 cu ft
3.8 cu ft

Cleaning

Easy clean porcelain basepan	
Pyrolytic self-clean	

Controls

Dial with illuminated halo	•
Dual control oven dials	•
Electric circuit	4 wire
High resolution display	•
Metal illuminated dials	•

Multi-language interface
Precise cooking with food probe
Recipe and food based functions
Sabbath mode
Smart appliance
Tilting touch screen interface

Gas Requirements

٠

Fitting and pipe	½ NPT, min. %″ ⊠ flex line
Supply Pressure (LPG)	11" to 14" W.C

Main oven features

Concealed Element	
Electronic oven control	
Full extension telescopic racks	
Internal light	
True convection	

Main oven functions

Air fry
Bake
Classic bake
Clean
Convection broil
Maxi broil
Number of oven functions
Pizza bake
Rapid proof

Roast Self cleaning Slow cook True convection Warm

Oven features

٠

15

Auto re-ignition system	•
Concealed element	•
Electronic oven control	•
Full extension telescopic sliding shelves	•
Internal light	true
True convection	•

Oven functions Air fry Bake Classic bake Clean Convection bake Convection Broil Dehydrate Dehydrate Maxi Broil Number of functions 15 Pastry bake Pizza bake Rapid proof Roast

Date: 17.12.2024 > 2

QUICK REFERENCE GUIDE > RHV3-484-L

Slow cook	•	SmartZoi
True convection	•	Vent trim
Warm	•	Zone brid

Oven performance

Bake	4600 W
Broil	3600 W
Broil power	4000 W
Main oven - True convection power	2500 W

Power requirements

Connection	4-prong grounding type [NEMA 14-50P plug]
Service	50 A
Supply	120 / 240 V, 60 Hz

Product dimensions

Depth	29 1/8 "
Height	35 3/4 - 36 3/4 "
Width	47 7/8 "

Rangetop features

Gentle heat
Heat settings
Induction cooking technology
Sealed range top

one im included

idging

Rangetop Performance

Left front zone rating	2100 (3700) W
Left rear zone rating	2100 (3700) W
Number of burners	4
Number of cooking zones	4
PowerBoost	•
PowerBoost all zones	up to 3700 W
Right front zone rating	2100 (3700) W
Right rear zone rating	2100 (3700) W

Recommended Back Guards Ventilation

Combustible situation	
Non combustible situation	

Recommended hood

Safety

٠ 9

ADA compliant
Pan detection system
Safety time out
Surface hot indicators

Secondary oven features 3/4 Extension racks

2

BGRV3-3048H

BGRV2-3048 /

HCB48-12_N (48"

BGRV2-1248

Professional Range Hood, Dual Blower)

.

Electronic oven control	•
Food probe	•
Internal light	•

Secondary oven functions Air fry Bake Classic bake Convection bake Convection broil Maxi broil Number of secondary oven functions 11 Pastry bake Pizza bake Rapid proof Roast Warm

Warranty

Parts and labor	Limited 2 years
SKU	82793

2

QUICK REFERENCE GUIDE > RHV3-484-L

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- 2D-DWG Dual Fuel Cooker with Backguard BGRV2-1248
- 2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048
- ↓ 2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ 2D-DWG Dual Fuel Range
- 2D-DXF Dual Fuel Cooker with Backguard BGRV2-1248
- ↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048
- ↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ 2D-DXF Dual Fuel Range
- ArchiCAD Dual Fuel Range
- ▲ Service & Warranty
- Installation Guide EN
- ↓ Installation Guide FR
- Planning Guide Professional Style Dial/Handle Accessories
- Planning Guide 48" Professional Ranges & Backguards
- ↓ Revit Dual Fuel Cooker
- Rhino Dual Fuel Cooker
- Sketchup Dual Fuel Cooker
- ↓ User Guide
- ↓ Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com