

90cm Series 3 Slide-Out Wall Rangehood

Series 3 | Contemporary

White

Ideal for compact kitchens, sliding out for use when you need quiet, efficient extraction above your cooktop.

- With two fan speeds, select the ideal extraction rate for your cooking
- Slides out for use when you need it, with maximum air movement of 340m³/hr
- Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

| | |
|--------|------------|
| Height | 181-185 mm |
| Width | 898 mm |
| Depth | 280-460 mm |

FEATURES & BENEFITS

Effective Extraction

This rangehood requires external ductions through the top. Ducted rangehoods such as this are more effective at removing steam, grease and odours.

Simple To Use

Simply flick a switch to turn this rangehood on or off, or to change between the two extraction speeds. A separate switch controls the bright halogen lights to provide illumination over your cooking surface.

Easy Cleaning

Two filters, consisting of layers of aluminium mesh, effectively trap grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless Integration

With white glass front panel handles and a brushed stainless steel finish, this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (included)

| | |
|------------------|--------|
| Aluminium filter | 792392 |
|------------------|--------|

Accessories (sold separately)

| | |
|-----------------------------|------------|
| Ducting solution | • |
| Eave ducting kit | PD-RHK125E |
| Light bulb | 791822 |
| Recirculation carbon filter | 792390 |
| Roof ducting kit | PD-RHK125T |
| Side wall ducting kit | PD-RHK125W |

Fan ratings

| | |
|----------------------|------------------------|
| Maximum air movement | 340 m ³ /hr |
| Maximum sound rating | 66 dBA |

Installation and cleaning

| | |
|-------------------------|---------------------------------|
| Air outlet size | 100mm (back) and 120mm (top) mm |
| Dishwasher safe filters | 2 |
| Ducted | Top extraction only |

Performance

| | |
|-----------------|---------|
| Extraction type | Surface |
| Fan speeds | 2 |

Power requirements

| | |
|----------------|-----------|
| Supply voltage | 220-240 V |
|----------------|-----------|

Product dimensions

| | |
|--------|------------|
| Depth | 280-460 mm |
| Height | 181-185 mm |
| Width | 898 mm |

Product information

| | |
|--------------|--------|
| Control type | Switch |
|--------------|--------|

Ventilation features

| | |
|------------|-----|
| Light type | LED |
|------------|-----|

SKU 50009

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓ Service & Warranty](#)
- [↓ Installation Guide](#)
- [↓ User Guide](#)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1300 650 590 W www.fisherpaykel.com