QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.09.2024 > 1

60cm Series 9 Integrated Triple Zone Refrigerator

Series 9 | Integrated

Panel Ready | Right Hinge



Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution – this model features three independent food zones taking cooling flexibility to a new level.*

- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory
- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation

- Convenient access to fresh, chilled water with internal water dispenser
- · Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm
Width 592 mm
Depth 576 mm

FEATURES & BENEFITS

Three Levels Of Freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Slimline Water Dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories (included)

Hinge change (from right hinge to left hinge)

QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.09.2024 > 2

Accessories (sold separately)		Door alarm	•	Amperage	10 A	
Door panel set stainless steel	Right & Left hinge RD6019	Internal water dispenser	•	Supply frequency	50 Hz	
		LED bin lighting	•	Supply voltage	230 V	
Handle kit Classic	AHCLRDSF	LED ceiling lighting	•			
Handle kit Contemporary round, aluminium	AHSRDSF	LED side lighting	•			
Handle kit Contemporary square fine, aluminium	AHD5RDSF	Smart appliance	•	Product dimensions		
Handle kit Contemporary square fine, black	AHD5RDSFB	SmartTouch control panel	•	Depth	576 mm	
Handle kit Professional round flush	AHP3RDSF	Stackable bottle holders	2	Height	1870 mm	
Joiner kit	AJRS19LR	Water tank capacity	1 L	Width	592 mm	
Toe kick stainless steel 1200mm	AKRS12010	-		-		
Toe kick stainless steel 1800mm	AKRS18010	Installation Dimensions		Warranty		
Toe kick stainless steel 600mm	AKRS06010	Minimum inside width of cabinetry frame	600 mm	Parts and labour	2 years	
Water filter replacement	847200 - FWC3	Minimum internal depth of cabinetry	600 mm	Sealed system parts only	5 years	
		Minimum internal height of cabinetry	1880 mm	Sedied system parts only	5 years	
Capacity						
Total gross capacity	330 L	Performance		SKU	26197	
Volume	306 L					
Volume refrigerator	306 L	ActiveSmart™ Foodcare	•	The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these		
		Adaptive defrost	•			
		Frost free	•	dimensions and specifications may change at any	time. You should therefore	
Consumption		Humidity control system	•	check with Fisher & Paykel's Customer Care Centr correctly describes the model currently available.	· -	
Energy rating	3.5 star	Humidity controlled crisper bins	4	Appliances Ltd 2020		
Energy usage	175kWh/year	Inverter controlled compressor	•			
In-use energy carbon emissions estimate	23.7kgCO2e/year	Sabbath mode	•			
		Triple evaporator	•	Other product downloads available at fish	erpaykel.com	
		Variable food modes	Pantry; Fridge; Chill			
Features		Variable temperature zones	3			
Adjustable door shelves	4		•		anel	
Adjustable glass cantilevered shelves	•				nel	
Covered door shelves	1	Power requirements				

QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.09.2024 > 3

- Energy Label
- ↓ Service & Warranty
- ↓ Installation Guide Integrated Refrigeration
- Revit 18 Refrigerator
- ↓ Rhino 5 Refrigerator
- Rhino 5 Refrigerator with Custom Panel
- Rhino 5 Refrigerator Door with Classic Round Handle
- ↓ Rhino 5 Refrigerator Door with Contemporary Round Handle
- Rhino 5 Refrigerator Door with Professional Round Flush
- ↓ Rhino 5 Refrigerator Door with Square Fine Black Handle
- ↓ Rhino 5 Refrigerator Door with Square Fine Handle
- ↓ Sketchup 8 Refrigerator
- ↓ Sketchup 8 Refrigerator with Custom Panel
- ↓ Sketchup 8 Refrigerator Door with Classic Round Handle
- Sketchup 8 Refrigerator Door with Professional Round Flush
- ↓ Sketchup 8 Refrigerator Door with Square Fine Black Handle
- Sketchup 8 Refrigerator Door with Square Fine Handle
- User Guide Integrated Refrigerator & Freezer

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 0800 372 273 Wwww.fisherpaykel.com