# 90cm Series 7 Integrated Insert Wall Rangehood


	Width
Series 7   Integrated	Depth
Stainless Steel and Glass	

With edge-to-edge extraction, this rangehood is perfectly hidden away in your cabinetry.

- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful maximum air movement of 780m<sup>3</sup>/hr
- Energy-efficient LED lighting to illuminate your cooking surface
- Wi-Fi enabled for notifications through the SmartHQ<sup>™</sup> app

# DIMENSIONS

Height	316 mm
Width	830 mm
Depth	280 mm



# **FEATURES & BENEFITS**

### Achieve The Invisible

This stylish rangehood fits seamlessly into your kitchen cabinetry, providing ventilation that is as discreet as it is powerful.

## Effective Extraction

cooking is finished so the timer keeps the hood working for up to 15 minutes before automatically turning off.

## Easy Cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe, while the glass and stainless steel finish is easily wiped clean. The SmartHQ<sup>™</sup> app will notify you when to clean the filter to ensure you get the best performance out of your rangehood.

## **Quality Materials**

This rangehood comes in a sleek black glass finish with a real stainless steel frame.

## Full Surface Lighting

Low energy, dimmable LED lights provide superb illumination of the entire cooking surface.

# SPECIFICATIONS

## Accessories (included)

Aluminium filter

792943

## Accessories (sold separately)

Eave ducting kit	PD-RHK150E
Light bulb	requires service to replace
Recirculation carbon filter	793599
Roof ducting kit	PD-RHK150T
Side wall ducting kit	PD-RHK150W

## QUICK REFERENCE GUIDE > HP90IDCHX4

Maximum air movement	780 m³/hı
Installation and cleaning	
Air outlet size	150 & 120 mm
Dishwasher safe filters	2
Ducted	Top extraction
Recirculation	Optional - top extractior
Performance	
Extraction type	Perimeter
Fan speeds	3
Fan speeds + boost	•
Filter type	Mesh with
	perimeter extractior
Number of filters	2
Power requirements	
Supply frequency	50 Hz
Supply voltage	220 - 240 V
Product dimensions	
Depth	280 mm
Height	316 mm
Width	830 mm

#### **Product information**

Control type	Capacitive touch
Ventilation features	
Auto-off/Run-on timer	•
Dimmable lights	•
Filter cleaning alert	•
Light type	LED strip
Timer function	•
Warranty	
Parts and labour	2 years

SKU 50190

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

#### Other product downloads available at fisherpaykel.com

Service & Warranty

Where applicable:

### Date: 17.12.2024 > 2

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T +65 6741 0777 Wwww.fisherpaykel.com