QUICK REFERENCE GUIDE > WB30SPEX1

30" Series 9 Professional Warming Drawer

Series 9 | Professional

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook. Pair with a Professional-style oven for design cohesion.

- A companion product, designed to match with other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- · Easy to clean smooth-glass base

 Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	10 11/16 "
Width	29 15/16 "
Depth	22 3/8 "

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes in brushed stainless steel, for seamless pairing with our matching ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy To Clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy To Use

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe And Sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories (included)		
Wire shelf		

Capacity

Accessory rack maximum allowable weight	42lb
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55 lbs
Place settings	16
Usable depth	16 1/16 "
Usable height	9 1/16 "
Usable width	21 1/2 "

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
Automatic timers	30′, 45′, 1h, 2h, 4h, 6h
Electronic capacitive touch controls	•
On/Off indicator	•
Pre-set heating functions	•

QUICK REFERENCE GUIDE > WB30SPEX1

Supply voltage	110 V
Supply frequency	grounding-type 60 Hz
Power outlet	3-prong
Power requirements Amperage	10 A
Dower requirements	
Temperature range	95°F-185°F
Temperature levels	6
Low temperature cooking	•
Heated glass base and fan	•
Performance	
Warm	•
Slow cook	•
Rapid proof	•
Plates	•
Number of functions	6
Dehydrate	•
Cups	•
Functions	
Standby mode	•
Soft close drawer	•
Sabbath mode	

Product dimensions

Adjustable front door panel to align with surrounding cabinetry	•
Depth	22 3/8 "
Height	10 11/16 "
Width	29 15/16 "
Safety	
Automatic turn off after 12 hours	•
Full extension slides	•
SKU	82115

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

2D-DWG Warming Drawer

Companions

<u> </u>	2D-DXF Warming Drawer
<u>↓</u>	Archicad Warming Drawer
<u>↓</u>	Service & Warranty
<u>↓</u>	Guide d'installation FR
↓	Installation Guide
<u>↓</u>	Planning Guide EN - Professional 30" Built-in Ovens and Companions
<u>↓</u>	Planning Guide Professional Style Dial/Handle Accessories
_ ↓	Planning Guide FR - Professional 30" Built-in Ovens and

→ Planning Guide SP - Professional 30" Built-in Ovens and Companions

Revit Warming Drawer

Rhino Warming Drawer

Sketchup Warming Drawer

Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

