QUICK REFERENCE GUIDE > RGV3-486GD-N Date: 17.12.2024 > 1

48" Series 7 Professional 6 Burner Griddle Gas Range, Natural Gas

Series 7 | Professional

Stainless Steel | Natural Gas



With Professional styling, this large range has six burners delivering powerful high heat, a griddle and two gas ovens.

- Griddle with burners that deliver up to 23,500 BTU heat per burner, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes

Made from quality materials and real stainless steel

DIMENSIONS

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "

FEATURES & BENEFITS

Generous Capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey. The griddle plate allows you to cook several foods at once.

Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total Control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Burner ratings

| Maximum burner power | 23500 BTU |
|----------------------|------------|
| Power back centre | 18500BTU |
| Power back left | 18500BTU |
| Power back right | 18500BTU |
| Power front centre | 18500BTU |
| Power front left | 23500BTU |
| Power front right | 18500BTU |
| Power griddle | 16500BTU |
| Total cooktop power | 132500 BTU |

Capacity

| Shelf positions (main oven) | 5 |
|-------------------------------|-----------|
| Shelf positions (second oven) | 5 |
| Total capacity (main oven) | 5.3 cu ft |
| Total capacity second oven | 2.4 cu ft |
| Usable capacity (main oven) | 3.9 cu ft |

Cleaning

Easy clean porcelain basepan •

| Controls | | Infrared Broiler | • | Rangetop features | |
|---|-------------------|-----------------------------|------------------------|-------------------------------------|-----------------------------|
| Metal illuminated dials | • | Internal light | true | Sealed range top | • |
| | | | | Vent trim included | • |
| Gas Requirements | | Oven functions | | | |
| Fitting and pipe | ½ NPT, min. 5%" 🛚 | Bake | • | Rangetop Performance | |
| | flex line | Broil | • | Number of burners | 6 |
| Supply Pressure (natural gas) | 6" to 9" W.C | Convection bake | • | | |
| | | Number of functions | 4 | | |
| | | Slow cook | • | Recommended Back Guards Ventilation | |
| Main oven features | | | | Combustible situation | BGRV3-3048H |
| Broil pan Electronic oven control | • | Oven performance | | Non combustible situation | BGRV2-3048 / BGRV2-1248 |
| Full extension telescopic racks | • | Bake power | 19700BTU | Recommended hood | HCB48-12_N (48" |
| Infrared broiler | • | Broil | 18500 BTU | | Professional Range Hood, |
| Internal light | • | Secondary oven - Bake power | 18000BTU | | Dual Blower) |
| Main oven functions | | Power requirements | | Safety | |
| Bake | • | Connection | 3-prong | ADA compliant | • |
| Broil | • | | grounding type plug | | |
| Convection bake | • | Service | 15 A | Secondary oven features | |
| Number of oven functions | 4 | Supply | 120 V, 60 Hz | Secondary over realures | |
| Slow cook | • | | | 3/4 Extension racks | 2 |
| | | | | Electronic oven control | • |
| Over feeture | | Product dimensions | | Internal light | • |
| Oven features | | Depth | 29 1/8 " | | |
| Auto re-ignition system | • | Height | 35 3/4 - 36 3/4 " | Secondary oven functions | |
| Broil pan | • | Width | 47 7/8 " | - | |
| Electronic oven control | • | | | Bake | • |
| Full extension telescopic sliding shelves | • | | | Convection bake | • |
| | | | | Number of secondary oven functions | 4 |

QUICK REFERENCE GUIDE > RGV3-486GD-N Date: 17.12.2024 > 3

Proof •
Slow cook •

Warranty

Parts and labor Limited 2 years

SKU 82383

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- Data Sheet Professional Range
- ↓ Energy Label
- Service & Warranty

- ↓ Rhino Gas Range
- User Guide
- ↓ Guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 Wwww.fisherpaykel.com

FISHER & PAYKEL