Dual Fuel Range, 48", 4 Burners, 4 Induction Zones, Self-cleaning

Stainless Steel | Natural Gas




With both induction and gas cooktops and two convection ovens, you're ready to create a feast - guided by an intuitive touchscreen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 23,500 BTU, for seriously fast boiling
- Four induction cooking zones, which can be paired to form two SmartZones

• 6.9 cu ft total oven capacity across two oven cavities

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 "



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

On the gas side of the cooktop, Sealed dual flow burners deliver power up to 23,500 BTU, while the induction side delivers up to 3700W. This finely tuned cooktop provides instant and immediate control from the highest heat to the most gentle simmer.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, high-quality glass, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function. The induction zones only need a quick wipe after use to keep them clean.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers

QUICK REFERENCE GUIDE > RHV3-484-N

Branded coin end cap

Accessories (sold separately)	
Square handle option	AH-R48
Burner ratings	
Maximum burner power	23500 BTU
Power back left	18500BTU
Power back right	18500BTU
Power front left	23500BTU
Power front right	18500BTU
Total cooktop power	79000 BTU

Capacity

Shelf positions (main oven)	5
Shelf positions (second oven)	5
Total capacity (main oven)	4.8 cu ft
Total capacity second oven	2.1 cu ft
Usable capacity (main oven)	3.8 cu ft

Cleaning

Easy clean porcelain basepan Pyrolytic self-clean

Controls

Dial with illuminated halo

Dual control oven dials	
Electric circuit	4 w
High resolution display	
Metal illuminated dials	
Multi-language interface	
Precise cooking with food probe	
recipeAndFoodBasedFunctions	
Sabbath mode	
Smart appliance	
Tilting touch screen interface	
Wi-Fi connectivity	

Gas Requirements

٠

Fitting and pipe	½ NPT, min. %″ ⊠ flex line
Supply Pressure (natural gas)	6" to 9" W.C

Main oven features

Concealed Element
Electronic oven control
Full extension telescopic racks
Internal light
True convection

Main oven functions

Air fry		
Bake		
Classic bake		
Clean		

Convection broil ٠ • /ire Maxi broil Number of oven functions 15 ٠ Pizza bake ٠ Rapid proof ٠ Roast . Self cleaning . Slow cook . True convection . Warm

Oven features

Auto re-ignition system	•
Concealed element	•
Electronic oven control	•
Full extension telescopic sliding shelves	•
Internal light	true
True convection	•

Oven functions

.

٠

.

.

Air fry	•
Bake	•
Classic bake	•
Clean	•
Convection bake	•
Convection Broil	•
Dehydrate	•
Dehydrate	•
Maxi Broil	•

QUICK REFERENCE GUIDE > RHV3-484-N

Number of functions
Pastry bake
Pizza bake
Rapid proof
Roast
Slow cook
True convection
Warm

Oven performance

Bake	4600 W
Broil	3600 W
Broil power	4000 W
Main oven - True convection power	2500 W

Power Requirements

Connection	4-prong grounding type [NEMA 14-50P plug]
Service	50 A
Supply	120 / 240 V, 60 Hz

Product Dimensions

Depth	29 1/8 "
Height	35 3/4 - 36 3/4 "
Width	47 7/8 "

Rangetop features Gentle heat Heat settings Induction cooking technology Sealed range top SmartZone Vent trim included Zone bridging

9

.

2

٠

Rangetop Performance

15

.

Left front zone rating	2100 (3700) W
Left rear zone rating	2100 (3700) W
Number of burners	4
Number of cooking zones	4
PowerBoost	•
PowerBoost all zones	up to 3700 W
Right front zone rating	2100 (3700) W
Right rear zone rating	2100 (3700) W

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48" Professional Range Hood, Dual Blower)

Pan detection system • Safety time out • Surface hot indicators • Secondary oven features • 3/4 Extension racks 2 Electronic oven control • Food probe • Internal light •

Secondary oven functions Air fry Bake Classic bake Convection bake Convection broil Maxi broil Number of secondary oven functions 11 Pastry bake Pizza bake Rapid proof Roast Warm Warranty Parts and labor Limited 2 years

Safety

ADA compliant

Date: 28.06.2024 > 3

81890

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- ↓ 2D-DWG Dual Fuel Range
- ↓ 2D-DXF Dual Fuel Range
- ↓ 2D-DWG Dual Fuel Cooker with Backguard BGRV2-1248
- ▲ 2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048
- ↓ 2D-DWG Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-1248
- 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048
- ↓ 2D-DXF Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ ArchiCAD Dual Fuel Range
- ↓ Data Sheet Dual Fuel Cooker with Backguard BGRV2-1248
- ↓ Data Sheet Dual Fuel Cooker with Backguard BGRV2-3048
- ↓ Data Sheet Dual Fuel Cooker with Backguard BGRV2-3048H and Angled Trim
- ↓ Data Sheet Dual Fuel Range
- ↓ Service & Warranty

 $\overline{\mathbf{1}}$

 $\frac{1}{4}$

 \downarrow

- ↓ Installation Guide EN
- ↓ Guide d'installation FR
- Planning Guide Professional Style Dial/Handle Accessories
- Revit Dual Fuel Cooker
- Rhino Dual Fuel Cooker
- Sketchup Dual Fuel Cooker
- Specification Guide

User Guide

Where applicable:

↓

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com