QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 25.11.2025 > 1

# 60cm Series 9 Integrated Triple Zone Refrigerator

#### Integrated




Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution – this model features three independent food zones taking cooling flexibility to a new level.

- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation
- Convenient access to fresh, chilled water with internal water dispenser
- Easy-to-use touch-control panel and Wi-Fi capability

#### **DIMENSIONS**

Height 1870 mm
Width 592 mm
Depth 576 mm



## **FEATURES & BENEFITS**

#### Three Levels Of Freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

#### Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

#### Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

#### Slimline Water Dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

#### Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

#### Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

#### Ease Of Use

QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 25.11.2025 > 2

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

#### **SPECIFICATIONS**

# Accessories (included)

Hinge change (from right hinge to left hinge)

#### Accessories (sold separately)

Door panel set stainless steel	Right & Left hinge RD6019
Handle kit Classic	AHCLRDSF
Handle kit Contemporary round, aluminium	AHSRDSF
Handle kit Contemporary square fine, aluminium	AHD5RDSF
Handle kit Contemporary square fine, black	AHD5RDSFB
Joiner kit	AJRS19LR
Toe kick stainless steel 1200mm	AKR\$12010
Toe kick stainless steel 1800mm	AKR\$18010
Toe kick stainless steel 600mm	AKRS06010
Water filter replacement	847200 - FWC3

#### Capacity

Total gross capacity	330 L
Volume	306 L
Volume refrigerator	306 L

# Consumption

Energy rating	Grade 1
Features	
Adjustable door shelves	4
Adjustable glass cantilevered shelves	•
Covered door shelves	1
Door alarm	•
Internal water dispenser	•
LED bin lighting	•
LED ceiling lighting	•
LED side lighting	•
SmartTouch control panel	•
Stackable bottle holders	2
Water tank capacity	1 L
Installation Dimensions	
Minimum inside width of cabinetry frame	600 mm
Minimum internal depth of cabinetry	600 mm
Minimum internal height of cabinetry	1880 mm

# Performance

ActiveSmart™ Foodcare	
Adaptive defrost	
Frost free	
Humidity control system	
Humidity controlled crisper bins	
Inverter controlled compressor	
Sabbath mode	

Triple evaporator	•
Variable food modes	Pantry; Fridge; Chill
Variable temperature zones	3

# Power requirements

Rated current	10 /
Supply frequency	50 H
Supply voltage	230 \

# **Product dimensions**

Depth	576 mm
Height	1870 mm
Width	592 mm

SKU

600 mm
600 mm
1880 mm

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

26212

## Other product downloads available at fisherpaykel.com



DWG DWG





DWG Appliance with Custom Panel

**QUICK REFERENCE GUIDE >** RS6019S3RH1 Date: 25.11.2025 > 3

- DXF

- Archicac
- ↓ Declaration of Conformity (Chinese)
- ↓ Energy Label
- ↓ Planning Guide (English)
- ↓ Planning Guide (Chinese)
- ↓ Revit
- ↓ Rhino
- ↓ Rhino Appliance with Custom Panel
- ↓ Rhino Appliance with Door and Classic Round Handle
- Rhino Appliance with Door and Contemporary Round Handle
- Rhino Appliance with Door and Professional Round Flush
- ↓ Rhino Appliance with Door and Square Fine Black Handle
- Rhino Appliance with Door and Square Fine Handle
- ↓ SketchUp
- SketchUp Appliance with Custom Panel
- SketchUp Appliance with Door and Contemporary Round Handle
- SketchUp Appliance with Door and Professional Round Flush
- ↓ SketchUp Appliance with Door and Square Fine Black Handle
- SketchUp Appliance with Door and Square Fine Handle
- ↓ User Guide (English)
- User Guide (Chinese)
- J. Installation Video

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

#### Where applicable: