QUICK REFERENCE GUIDE > RS6121SLK3

# 61cm Series 11 Integrated Column Refrigerator

Series 11 | Integrated

Panel Ready | Left hinge



Install it separately or pair with another Column for true design freedom - this model is left hinge with stainless steel interior.


- ActiveSmart<sup>™</sup> technology helps keep food fresher for longer by constantly maintaining the ideal temperature.
- Variable Temperature Zone lets you change a compartment to Fridge, Pantry or Chill for optimal storage
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory

### **DIMENSIONS**

Height 2134 mm

Width 603 mm

Depth 610 mm



### **FEATURES & BENEFITS**

### Mix & Match

Integrated Column Refrigeration gives you the freedom to mix and match. Different sized Column Fridges and Freezers can be installed separately or paired. Finish them with our stainless steel door panels or customise to match your own kitchen cabinetry.

Perfect Fit

These models fit flush, with only 3mm gaps around them and no visible hinges or grilles. Our Integrated Column models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

# Clever Energy

Our ActiveSmart™ Foodcare Refrigerator Freezers adapt to daily use by cooling and defrosting only when needed. This means your fridge uses the energy it needs without compromising on food care.

## Appealing Illumination

Bright LEDs light up each ceiling, shelves, bins and trays in both refrigerator and freezer, making it easy to find your food and creating a welcoming glow in your kitchen for those midnight snacks.

### **Design Quality**

The premium design and quality finish includes a steel interior lining as well as soft-close, full extension metal shelf runners for easy access and robust glass shelving.

### Easy Install

Integrated Column Refrigerators and Freezers have been developed to make their installation easy. The joiner kit is included when pairing refrigerators and freezers. All models come with front adjustable levelling feet and they've been designed to easily slide into place as separate units.

# **SPECIFICATIONS**

### Accessories (sold separately)

Handle kit Classic

Handle kit Contemporary round, aluminium

AHSRDSF

Handle kit Contemporary square fine, aluminium

Handle kit Contemporary square fine, black

AHD5RDSFB

Handle kit Professional round flush Joiner Kit	AHP3RDSF AJ-RS21LR	Stackable bottle holders	4	Width	603 mm	
Toe kick stainless steel 1067mm	AKRS10710					
Toe kick stainless steel 1220mm	AKR\$12210	Installation Dimensions		Product information		
Toe kick stainless steel 1372mm	AKRS13710	Minimum inside width of cabinetry frame	610 mm	Packaged weight	137 kg	
Toe kick stainless steel 1828mm	AKRS18310	Minimum internal depth of cabinetry	635 mm	Unpackaged weight	117 kg	
Toe kick stainless steel 1981mm	AKRS19810	Minimum internal height of cabinetry	2134 mm		3	
Toe kick stainless steel 610mm	AKRS06110			-		
		_		Warranty		
		Performance		Parts and labour	5 years	
Capacity		ActiveSmart™ Foodcare	•	Sealed system parts only	5 years	
Total gross capacity	383 L	Adaptive defrost	•	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Volume	351 L	Dual evaporator	•			
Volume refrigerator	351 L	Frost free	•			
		Humidity control system	•	SKU	26639	
		Inverter controlled compressor	•			
Consumption		Noise emissions	·		ge apply to the specific	
Energy rating	С	Noise emissions class	D	product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020		
Energy usage	104kWh/year	Sabbath mode	•			
In-use energy carbon emissions estimate	20.7kgCO2e/year	Variable temperature zones	2			
Features		Power requirements		Other product downloads available at fishers	paykel.com	
Adjustable door shelves	4	Rated current	10 A		,	
Covered door shelves	1	Supply frequency	50 Hz	↓ 2D-DWG Integrated Column Fridge-Hin	ge	
Door alarm	•	Supply voltage	220 - 240 V			
Gallon door shelves	1				el Prep	
LED bin lighting	•				e	
LED ceiling lighting	•	Product dimensions				
LED side lighting	•	Depth	610 mm			
Smart appliance	•	Height	2134 mm	Data Sheet Integrated Column Fridge Dual Install (457mm + 610mm)		

QUICK REFERENCE GUIDE > RS6121SLK3 Date: 18.10.2024 > 3

- Data Sheet Integrated Column Fridge Dual Install (610mm + 610mm)
- Data Sheet Integrated Column Fridge Dual Install (610mm + 762mm)
- Data Sheet Integrated Column Fridge with Contemporary Square Handle Kit
- Data Sheet Integrated Column Fridge with Contemporary Round Handle Kit
- ↓ Declaration of Conformity Refrigeration with WiFi Capability
- ↓ Energy Label
- ↓ Service & Warranty
- ↓ Key Purchase Decisions Integrated Columns
- ↓ Product Information Sheet
- ↓ Specification Guide Integrated Column Fridge
- User Guide Integrated Refrigerator Freezer EN

### Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

