QUICK REFERENCE GUIDE > CPV2-485GDN N Date: 17.10.2024 > 1

48" Series 9 5 Burner + Griddle Gas Rangetop, Natural Gas

Series 9 | Professional

Stainless Steel | Natural Gas




A powerful five burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Your burners can deliver anything from very high 23,500 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- The stainless steel griddle is great for cooking anything from pancakes to bacon, grilled cheese to guesadillas

DIMENSIONS





FEATURES & BENEFITS

Perfect Heat

Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise Control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking Flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. Heavyweight stainless steel griddles can be set to desired temperatures and then maintained evenly across the entire griddle surface.

Information At A Glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Easy Cleaning

These cooktops have sealed burners and a single sheet cooking surface which, combined with a commercial-style stainless steel finish and dishwasher-safe grates, allow easy cleaning.

Complementary Design

Built to last with distinctive, bold styling, this rangetop is designed to match the Fisher & Paykel Professional style family of appliances.

SPECIFICATIONS

Burner ratings

Maximum burner power	Yes
Power back left	18500BTU
Power back right	18500BTU
Power front left	18500BTU
Power front right	18500BTU
Power griddle	24500BTU

Controls

Metal illuminated dials

QUICK REFERENCE GUIDE > CPV2-485GDN N Date: 17.10.2024 > 2

Power Requirements

Amperage
Supply frequency

Depth

Supply voltage

Product Dimensions

Sealed Dual Flow Burners™ Sealed range top	_
Sealed range top	5
	•
Simmer on all burners	10 °F

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020



Other product downloads available at fisherpaykel.com

\underline{ullet}	2D-DWG Gas Cooktop
<u>↓</u>	2D-DXF Gas Cooktop
<u>↓</u>	Archicad Gas Cooktop
<u></u>	Data Sheet Gas Cooktop
<u>↓</u>	Service & Warranty
\underline{ullet}	Installation Guide
<u></u>	Planning Guide Gas Cooktop
\underline{ullet}	Revit Gas Cooktop
\overline{ullet}	Rhino 5
$\overline{\underline{\downarrow}}$	Sketchup Gas Cooktop
<u>_</u>	User Guide
_	

Height	8 5/16 "
Width	47 7/8 "

Recommended Back Guards Ventilation

Minimum CFM	1200 BTU
Pro hood	VS48

Warranty

Parts and labor	2 years
SKU	71378

Where applicable:

15 A

60 Hz

120 V

28 "

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.