QUICK REFERENCE GUIDE > HF60LX4

Wall Rangehood, 60cm, Fixed

Series 3 | Contemporary

Stainless Steel




This stainless steel rangehood has Contemporary styling, extracting steam, grease and cooking odours quietly and efficiently.

- With three fan speeds, select the perfect extraction rate for your cooking
- Efficient maximum air movement of 185m³/hr
- · Dishwasher safe filters that are easy to remove and clean

DIMENSIONS

Height 120 mm
Width 598 mm
Depth 450 mm



FEATURES & BENEFITS

Easy Installation

This rangehood can be either externally ducted through the top or back or can recirculate air internally through its filters, making it perfect for apartments.

Simple Controls

Simply flick a switch to turn this rangehood on or off, or to change between three extraction speeds. A separate switch controls the bright halogen lights to provide illumination over your cooking surface.

Easy Cleaning

A filter, consisting of layers of aluminium mesh, effectively traps grease particles during extraction. They are easy to remove and dishwasher safe, or can be cleaned by hand in hot soapy water.

Seamless Integration

The brushed stainless steel finish on this rangehood is designed to match the rest of the Fisher & Paykel's kitchen appliance family.

SPECIFICATIONS

Accessories (sold separately)

Eave ducting kit	PD-RHK125E
Light bulb	792507
Recirculation carbon filter	792506
Roof ducting kit	PD-RHK125T
Side wall ducting kit	PD-RHK125W

Fan ratings

Maximum motor performance	350 cm/hr
Maximum pressured air movement EN61591	185 m³/hr
Maximum sound rating	58 dBA

Installation and cleaning

Recirculation Optional - front	Air outlet size	120 mm
Recirculation Optional - front	Dishwasher safe filters	1
•	Ducted	Top extraction
	Recirculation	Optional - front extraction

QUICK REFERENCE GUIDE > HF60LX4

Performance	•
-------------	---

Extraction type Surface
Fan speeds 3
Filter type Mesh
Number of filters 1

Power requirements

Supply frequency 50 Hz
Supply voltage 220-240 V

Product dimensions

 Depth
 450 mm

 Height
 120 mm

 Width
 598 mm

Product information

Control type Push Button

Ventilation features

Light type Incandescent

Warranty

Parts and labour 2 years

SKU 50010

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Service & Warranty



User & Installation Guide - Standard Rangehood

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 0800 372 273 Wwww.fisherpaykel.com