QUICK REFERENCE GUIDE > RS6121SLK3

Integrated Column Refrigerator, 61cm

Series 11 | Integrated

Panel Ready | Left hinge



Install it separately or pair with another Column for true design freedom - this model is left hinge with stainless steel interior.


- ActiveSmart™ technology helps keep food fresher for longer by constantly maintaining the ideal temperature.
- Variable Temperature Zone lets you change a compartment to Fridge, Pantry or Chill for optimal storage
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory

DIMENSIONS

 Height
 2134 mm

 Width
 603 mm

 Depth
 610 mm



FEATURES & BENEFITS

Mix & Match

Integrated Column Refrigeration gives you the freedom to mix and match. Different sized Column Fridges and Freezers can be installed separately or paired. Finish them with our stainless steel door panels or customise to match your own kitchen cabinetry.

Perfect Fit

These models fit flush, with only 3mm gaps around them and no visible hinges or grilles. Our Integrated Column models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Clever Energy

Our ActiveSmart™ Foodcare Refrigerator Freezers adapt to daily use by cooling and defrosting only when needed. This means your fridge uses the energy it needs without compromising on food care.

Appealing Illumination

Bright LEDs light up each ceiling, shelves, bins and trays in both refrigerator and freezer, making it easy to find your food and creating a welcoming glow in your kitchen for those midnight snacks.

Design Quality

The premium design and quality finish includes a steel interior lining as well as soft-close, full extension metal shelf runners for easy access and robust glass shelving.

Easy Install

Integrated Column Refrigerators and Freezers have been developed to make their installation easy. The joiner kit is included when pairing refrigerators and freezers. All models come with front adjustable levelling feet and they've been designed to easily slide into place as separate units.

SPECIFICATIONS

Accessories (sold separately)

Handle kit Contemporary round, aluminium

Handle kit Contemporary square fine, aluminium

Handle kit Contemporary square fine, black

Handle kit Contemporary square, aluminium

AHD5RDSFB

AHD5RDSFB

QUICK REFERENCE GUIDE > RS6121SLK3

Joiner Kit	AJ-RS21LR	Smart appliance UK IE	•	Depth	610 mm	
Toe kick stainless steel 1067mm	AKRS10710	Stackable bottle holders	4	Height	2134 mm	
Toe kick stainless steel 1220mm	AKRS12210	Wi-Fi connectivity	•	Width	603 mm	
Toe kick stainless steel 1372mm	AKRS13710					
Toe kick stainless steel 1828mm	AKRS18310					
Toe kick stainless steel 1981mm	AKRS19810	Installation Dimensions		Product information		
Toe kick stainless steel 610mm	AKRS06110	Minimum inside width of cabinetry frame	610 mm	Packaged weight	137 kg	
		Minimum internal depth of cabinetry	635 mm	Unpackaged weight	117 kg	
		Minimum internal height of cabinetry	2134 mm		_	
Capacity						
Total gross capacity	383 L			Warranty		
Volume	351 L	Performance		Parts and labour	5 years	
Volume refrigerator	351 L	ActiveSmart™ Foodcare	•	Sealed system parts only	5 years	
		Adaptive defrost	•			
		Dual evaporator	•			
Consumption		Frost free	•	01/11	0.5520	
Energy rating	С	Humidity control system	•	SKU	26639	
Energy usage	104kWh/year	Inverter controlled compressor	•			
In-use energy carbon emissions estimate	20.7kgCO2e/year	Noise emissions	42 dBA	The product dimensions and specifications in this page apply to the specific		
		Noise emissions class	D product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefo			
		Sabbath mode	•	check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020		
Features		Variable temperature zones	2			
Adjustable door shelves	4			Appliances Ltd 2020		
Covered door shelves	1	·				
Door alarm	•	Power requirements		Other product downloads available at fish	erpaykel.com	
Gallon door shelves	1	Rated current	10 A			
LED bin lighting	•	Supply frequency	50 Hz		Hinge	
LED ceiling lighting	•	Supply voltage	220 - 240 V			
LED side lighting	•				Panel Prep	
Smart appliance AU NZ	•				inge	
Smart appliance EU	•	Product dimensions				
				± 2D-DXF Integrated Column Fridge-Pa	anei Prep	

QUICK REFERENCE GUIDE > RS6121SLK3

Date: 20.06.2024 > 3

- Data Sheet Integrated Column Fridge Dual Install (457mm + 610mm)
- Data Sheet Integrated Column Fridge Dual Install (610mm + 610mm)
- Data Sheet Integrated Column Fridge Dual Install (610mm + 762mm)
- Data Sheet Integrated Column Fridge with Contemporary Square Handle Kit
- Data Sheet Integrated Column Fridge with Contemporary
 Round Handle Kit
- ↓ Declaration of Conformity Refrigeration with WiFi Capability
- ↓ Energy Label
- ↓ Installation Guide Integrated Column Refrigerator
- Key Purchase Decisions Integrated Columns
- J. Product Information Sheet
- ↓ Specification Guide Integrated Column Fridge
- ↓ User Guide Integrated Refrigerator Freezer EN

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

