

Warming Drawer, 30"

Series 9 | Contemporary

Black Glass



Serve meals hot and directly from a pre-heated plate thanks to our panel-ready, warming drawer.

- Integrates with surrounding cabinetry for a seamless look
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	10 11/16 "
Width	29 15/16 "
Depth	22 5/16 "

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes with the option of a stylish black glass panel or elegant grey glass panel, for seamless pairing with our Minimal or Contemporary style ovens. Door panel must be purchased separately.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof for proofing dough, Dehydrate for drying foods such as meat, fruit and herbs and Slow Cook, ideal for finishing of seared meats, casseroles, stews and braises.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking. You can even rest meat after a traditional roast in the oven and proof dough for bread making and pizza.

Added Convenience

Handle-free, push-to-open with intuitive touch controls, our warming drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Easy To Clean

Cleaning and care of the warming drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Safe And Sound

With automatic switch-off and delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

Sized To Suit

With enough room to gently heat 16 place settings, 20 cappuccino cups or 42 espresso cups, our tall warming drawer is an ideal kitchen companion.

SPECIFICATIONS

Accessories (included)

Wire shelf	1
------------	---

Capacity

Accessory rack maximum allowable weight	42lb
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55 lbs
Place settings	16
Usable depth	16 1/16 "
Usable height	9 1/16 "
Usable width	27 1/2 "

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
----------------	---

Automatic timers	30', 45', 1h, 2h, 4h, 6h	Supply frequency	60 Hz	↓	Guide d'installation FR
Electronic capacitive touch controls	•	Supply voltage	110 V	↓	Guía de instalación SP
On/Off indicator	•			↓	Planning Guide - Contemporary 30" Built-in Ovens and Companions
Pre-set heating functions	•	Product Dimensions		↓	Planning Guide - Minimal 30" Built-in Ovens and Companions
Push-to-open drawer	•	Adjustable front door panel to align with surrounding cabinetry	•	↓	User Guide Warming Drawer
Sabbath mode	•	Depth	22 5/16 "	↓	User Guide Warming Drawer FR
Soft close drawer	•	Height	10 11/16 "	↓	User Guide Warming Drawer SP
Standby mode	•	Width	29 15/16 "		
Functions		Safety			Where applicable:
Cups	•	Automatic turn off after 12 hours	•		All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.
Dehydrate	•	Full extension slides	•		
Number of functions	6				
Plates	•				
Rapid proof	•				
Slow cook	•	SKU	83086		
Warm	•				
Performance		The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020			
Heated glass base and fan	•				
Low temperature cooking	•				
Temperature levels	6				
Temperature range	95°F-185°F				
Power Requirements		Other product downloads available at fisherpaykel.com			
Amperage	10 A	↓	2D-DWG Warming Drawer		
Power outlet	3-prong grounding-type	↓	2D-DXF Warming Drawer		
		↓	Service & Warranty		
		↓	Installation Guide Warming Drawer EN		



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 W [www.fisherpaykel.com](#)