QUICK REFERENCE GUIDE > RGV3-488L

# Gas Range, 48", 8 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- · Made from quality materials and real stainless steel

## **DIMENSIONS**

Height 35 3/4 - 36 3/4 "

Width 47 7/8 "

Depth 29 1/8 "

# **FEATURES & BENEFITS**

## **Generous Capacity**

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

### **Cooktop Power**

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

## Cooking Flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

#### Easy To Clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

# **Design Quality**

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

### **Total Control**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

# **SPECIFICATIONS**

Burner ratings	
Maximum burner power	17000 BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power centre	15000BTU
Power front centre (2)	15000BTU
Power front left	17000BTU
Power front right	17000BTU
Total cooktop power	116000 BTU

#### Capacity

Shelf positions	5
Total capacity (main oven)	5.3 cu ft
Total capacity second oven	2.4 cu ft
Usable capacity (main oven)	3.9 cu ft

#### Cleaning

Easy clean porcelain basepan

## Controls

Electric circuit 3 wire

QUICK REFERENCE GUIDE > RGV3-488L Date: 05.07.2024 > 2

Metal illuminated dials •		Oven functions		Safety	
		Bake	•	ADA compliant	•
Co. D. minoranto		Broil	•	Full extension telescopic sliding shelves	•
Gas Requirements		Convection bake	•		
Fitting and pipe	½ NPT, min. %″ ∑ flex line	Slow cook	•	Secondary oven features	
Supply Pressure (LPG)	11" to 14" W.C			•	
		Power requirements		3/4 Extension racks	2
				Electronic oven control	•
Main oven features		Service	15 A	Internal light	•
Broil pan	•	Supply	120 V, 60 Hz		
Electronic oven control	•			Secondary oven functions	
Full extension telescopic racks	•	Product dimensions		Bake	
Internal light	•	Depth	29 1/8 "	Convection bake	•
		Depth (excluding handles)	29 1/8 "	Number of secondary oven functions	4
Main oven functions		Height	35 3/4 - 36 3/4 "	Proof	•
Bake		Width	47 7/8 "	Slow cook	•
Broil					
Convection bake	•				
Number of oven functions	4	Rangetop features		SKU	81995
Slow cook	•	Sealed range top	•	3.00	01333
Sion Cook		Vent trim included	•		
				The product dimensions and specifications in this page apply	
Oven features				product and model. Under our policy of continuous improved dimensions and specifications may change at any time. You:	
Auto re-ignition system	•	Recommended Back Guards Ventilation		check with Fisher & Paykel's Customer Care Centre to ensure	
Electronic oven control	•	Combustible situation	BGRV3-3048H	correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020	
Full extension telescopic sliding shelves	•	Non combustible situation	BGRV2-3048 / BGRV2-1248		
Internal light	true	Recommended hood	HCB48-12_N (48"		
Titanium coated, illuminated metal dials	•		Professional Range Hood, Dual Blower)	Other product downloads available at fisherpaykel.com	
			·	→ ArchiCAD Gas Range	

QUICK REFERENCE GUIDE > RGV3-488L Date: 05.07.2024 > 3

 $\overline{\mathbf{\Lambda}}$ 

Service & Warranty

 $\overline{\mathbf{\Lambda}}$ 

Revit Gas Range



Rhino Gas Range



Sketchup Gas Range



User Guide



Guide d'utilisation FR

# Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com