Dual Fuel Range, 36", 6 Burners, Self-cleaning, LPG

Series 9	1	Professional

Stainless Steel | LPG




Get the best of gas and convection technology in this striking range with intuitive touchscreen and specialized cooking functions.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 19,000 BTU, for seriously fast boiling
- 4.8 cu ft total oven capacity
- Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	35 7/8 "
Depth	29 1/8 "



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Featuring a large 4.8 cu ft total capacity convection oven, with enough room to fit a 32 lb turkey and full-size baking sheets.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 19,000 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories (included)	
Adjustable feet covers	•
Branded coin end cap	•

Accessories (sold separately)

Square handle option	AH-R36
Wok grate included	No

QUICK REFERENCE GUIDE > RDV3-366-L

Burner ratings

Maximum burner power	19000 BTU
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	19000BTU
Power front right	19000BTU
Total cooktop power	92000 BTU

Capacity	
Shelf positions	5
Total capacity	4.8 cu ft
Usable capacity	3.8 cu ft

٠

Cleaning

Easy clean porcelain basepan	
Pyrolytic self-clean	

Controls	
----------	--

Dial with illuminated halo	•
Electric circuit	4 wire
High resolution display	•
Metal illuminated dials	•
Multi-language interface	•
Precise cooking with food probe	•
recipeAndFoodBasedFunctions	•
Sabbath mode	•

Smart appliance	•
Tilting touch screen interface	•
Wi-Fi connectivity	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %″ X flex line
Supply Pressure (LPG)	11" to 14" W.C
Main oven functions	
Warm	•
Oven features	
Auto re-ignition system	•
Concealed element	•
Electronic oven control	•
Food probe	•
Full extension telescopic sliding shelves	•
Internal light	true
Large broil pan	•
Self-clean proof side racks	•
True convection	•
Oven functions	

Air fry
Bake
Classic bake
Clean

Convection bake	•
Convection Broil	•
Dehydrate	•
Dehydrate	•
Maxi Broil	•
Number of functions	15
Pastry bake	•
Pizza bake	•
Rapid proof	•
Roast	•
Slow cook	•
True convection	•
Warm	•

Oven performance

Main oven - True convection power	2500 W
Power Requirements	
Rated current	30 A
Supply frequency	60 Hz
Product Dimensions	
Depth	29 1/8
Depth (excluding handles)	29 1/8 '
Height	35 3/4 - 36 3/4 '
Width	35 7/8

Rangetop features

٠

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RDV3-366-L

Vent trim included

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3036H		
Non combustible situation	BGRV2-3036 / BGRV2-1236		
Recommended hood	HCB36-6_N (36" Professional Range Hood) / HCB36-12_N (36" Professional Range Hood, Dual Blower)		
Safety			
ADA compliant	•		
Full extension telescopic sliding shelves	•		
Secondary oven features			
Food probe	•		
Warranty			
Parts and labor	Limited 2 years		
SKU	81899		

Other product downloads available at fisherpaykel.com

- 2D-DWG Dual Fuel Range
- 2D-DXF Dual Fuel Range
- 2D-DWG Dual Fuel Range with Backguard BGRV2-1236
- 2D-DWG Dual Fuel Range with Backguard BGRV2-3036
- ↓ 2D-DWG Dual Fuel Range with Backguard BGRV2-3036H and Angled Trim
- ↓ 2D-DXF Dual Fuel Range with Backguard BGRV2-1236
- 2D-DXF Dual Fuel Range with Backguard-BGRV2-3036
- ↓ 2D-DXF Dual Fuel Range with Backguard-BGRV2-3036H and Angled Trim
- ArchiCAD Dual Fuel Range
- ↓ Data Sheet Dual Fuel Range with Backguard BGRV2-1236
- ↓ Data Sheet Dual Fuel Range with Backguard BGRV2-3036
- ↓ Data Sheet Dual Fuel Range with Backguard BGRV2-3036H and Angled Trim
- ↓ Data Sheet Dual Fuel Range
- ↓ Service & Warranty

 \downarrow

1

T

- Installation Guide EN
- Guide d'installation FR
- Planning Guide Professional Style Dial/Handle Accessories
- Revit Dual Fuel Range
- Rhino Dual Fuel Range
- ↓ Sketchup Dual Fuel Range
- , Specification Guide Dual Fuel Range
- User Guide Professional Range EN

Where applicable:

Date: 28.06.2024 > 3

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 Wwww.fisherpaykel.com

FISHER & PAYKEL