QUICK REFERENCE GUIDE > RDV3-485GD-N Date: 17.10.2024 > 1

48" Series 9 Professional 5 Burner + Griddle Dual Fuel Pyrolytic Range, NG

Series 9 | Professional

Stainless Steel | Natural Gas




With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Gas cooktop with griddle and a top burner heat up to 23,500 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities

Ensure perfect results with the food probe, included

DIMENSIONS

Height	35 3/4 - 36 3/4 "
Width	47 7/8 "
Depth	29 1/8 "



FEATURES & BENEFITS

Cook With Confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous Capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 23,500 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy To Clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories (included)

Adjustable feet covers •

Branded coin end cap •

Accessories (sold separately)		Electric circuit	4 wire	Convection broil	•
Square handle option AH-R48	AH-R48	High resolution display	•	Maxi broil	•
		Metal illuminated dials	•	Number of oven functions	15
		Multi-language interface	•	Pizza bake	•
Burner ratings		Precise cooking with food probe	•	Rapid proof	•
Maximum burner power	23500 BTU	$recipe {\sf AndFoodBasedFunctions}$	•	Roast	•
Power back centre	23500BTU	Sabbath mode	•	Slow cook	•
Power back left	18500BTU	Smart appliance	•	True convection	•
Power back right	18500BTU	Tilting touch screen interface	•	Warm	•
Power front left	18500BTU				
Power front right	18500BTU	Coo Bonisino mando		Over feetimes	
Power griddle	24000BTU	Gas Requirements		Oven features	
Total cooktop power	121500 BTU	Fitting and pipe	½ NPT, min. 5⁄8″ ∑ flex line	Auto re-ignition system	•
		Supply Pressure (natural gas)	6" to 9" W.C	Concealed element	•
		Supply Tressure (natural gas)	0 10 5 m.c	Electronic oven control	•
Capacity				Full extension telescopic sliding shelves	•
Shelf positions (main oven)	5	Main oven features		Internal light	true
Shelf positions (second oven)	5	Concealed Element	•	Titanium coated, illuminated metal dials	•
Total capacity (main oven)	4.8 cu ft	Electronic oven control	•		
Total capacity second oven	2.1 cu ft	Full extension telescopic racks	•	Oven functions	
Usable capacity (main oven)	3.8 cu ft	Internal light	•		
		Large broil pan	•	Air fry	•
		Self-clean proof side racks	•	Bake	•
Cleaning				Classic bake	•
Easy clean porcelain basepan	•			Clean	•
Pyrolytic self-clean	•	Main oven functions		Convection bake	•
		Air fry	•	Convection Broil	•
		Bake	•	Dehydrate	•
Controls		Classic bake	•	Dehydrate	•
Dial with illuminated halo	•	Clean	•	Maxi Broil	•
Dual control oven dials	•	Convection bake	•	Number of functions	15

QUICK REFERENCE GUIDE > RDV3-485GD-N Date: 17.10.2024 > 3

Pastry bake	•	Width	47 7/8 "	Bake •
Pizza bake	•			Classic bake •
Rapid proof	•			Convection bake •
Roast	•	Rangetop features		Convection broil •
Slow cook	•	Sealed range top	•	Maxi broil •
True convection	•	Vent trim included	•	Number of secondary oven functions 11
Warm	•			Pastry bake •
				Pizza bake •
		Recommended Back Guards Ventilation		Rapid proof •
Oven performance		Combustible situation	BGRV3-3048H	Roast •
Bake power	4600	Non combustible situation	BGRV2-3048 /	Warm •
Broil	3600 W		BGRV2-1248	
Main oven - True convection power	2500 W	Recommended hood	HCB48-12_N (48"" Professional Range Hood, Dual Blower)	SKU 81894
Power Requirements				
Connection	4-prong grounding type [NEMA 14-50 plug] 50 A	Safety ADA compliant		The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel
Supply	120 / 240 V, 60 Hz	Secondary oven features		Appliances Ltd 2020
		3/4 Extension racks	2	Other product downloads available at fisherpaykel.com
Product Details		Concealed element	•	
Self Cleaning Sf	Yes	Electronic oven control	•	
Self Clearing Si	163	Food probe	•	
		Internal light	•	
Product Dimensions				Service & Warranty Planning Childs Professional Style Dist/Handle Assessmine
Depth	29 1/8 "	Secondary oven functions	_	 ✓ Planning Guide Professional Style Dial/Handle Accessories ✓ Revit Dual Fuel Range
Depth (excluding handles)	2918 mm	Air fry	•	★ Rhino Dual Fuel Range Cleated to Dual Fuel Range
Height	35 3/4 - 36 3/4 "	, 11 y	-	

QUICK REFERENCE GUIDE > RDV3-485GD-N



User Guide EN

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com