QUICK REFERENCE GUIDE > OR90SPI6X1

90cm Series 9 Classic 5 Zone Induction Pyrolytic Cooker, 2 SmartZones

Series 9 | Professional

Stainless Steel



Professional style and performance, with a large oven and five cooktop zones that can be paired to create an expansive cook zone.

- Large convection oven with 140L total capacity
- Nine functions plus Rotisserie, including Pastry Bake, Pizza Mode and Rapid Proof
- Non-tip full-extension shelves for safe removal of hot dishes

 Pyrolytic self-cleaning oven cycle breaks down food residue for an easy clean

DIMENSIONS

 Height
 898-946 mm

 Width
 897 mm

 Depth
 600 mm

FEATURES & BENEFITS

Multi-Shelf Cooking

Our AeroTech™ system circulates heat evenly for a consistent temperature throughout the cavity, helping you achieve perfect results even when using multiple shelves.

Quality And Durability

Every detail has been carefully crafted. The solid, perfectly balanced soft-close door, durable cooktop and glowing halo dials all add up to a premium freestanding cooker.

Power & Control

Instant and immediate control from the highest to the gentlest heat. The finely tuned cooktop controls let you sear, stir fry or simmer a delicate sauce to perfection.

Easy To Clean

Cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new. The pyrolytic self-clean oven cycle breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth.

Even Heat

Accurate, electronically controlled oven heat ensures a great result every time.

Large Capacity Oven

The generous 140L total capacity oven gives you plenty of space to cook multiple dishes at once.

SPECIFICATIONS

Accessories (included)

Flat wire shelf	1
Full extension sliding shelves	2 sets (part 578744)
Pyrolytic proof shelf runners	1 set
Roasting dish and grill rack set	1 set
Rotisserie set	1 set
Step down wire shelf	•

Accessories (sold separately)

Kick strip, stainless steel (or	tional) KICKOR90X1
---------------------------------	--------------------

Capacity

Shelf positions	6
Total capacity	140 L
Usable capacity	120 L

Cleaning

Acid resistant graphite enamel	•
Drop down grill element	•
Flat easy clean glass surface	

QUICK REFERENCE GUIDE > OR90SPI6X1 Date: 24.09.2024 > 2

Pyrolytic proof shelf runners	•	Oven features		Power requirements	
Pyrolytic self-clean	•	AeroTech™ technology	•	Amperage	68 A
Removable oven door	•	Automatic rapid pre-heat	•	Supply frequency	50 Hz
Removable oven door inner glass	•	Convection	•	Supply voltage	220-240 V
Removable shelf runners	•	Electronic oven control	•		
		Full extension telescopic sliding shelves	•		
Controls		Internal light	4 x 25W halogen (2 side & 2 top)	Product dimensions	500
Audio feedback	•	Soft open/close door	•	Depth	600 mm 898-946 mm
Automatic cooking/minute timer	•	Twin cavity fans	•	Height	898-946 mm 897 mm
Automatic pre-set temperatures	•	Warming drawer	•	Width	697 111111
Celsius/Fahrenheit temperature	•				
Dial with illuminated halo	•			Rangetop features	
Electronic clock	•	Oven functions		Dual colour display	
High resolution display	•	Bake	•	Gentle heat	
Laser etched graphics	•	Fan bake	•	Heat settings	9
Precise electronic temperature control	•	Fan forced	•	Hob rail	•
Sabbath mode	•	fanGrill	•	Hob rear trim	60 mm
Toughened fused glass graphics	•	Grill	•	Induction cooking technology	•
Turned stainless steel clock buttons	•	Number of functions	9 + rotisserie	PowerBoost	true
Turned stainless steel clock crown (dial)	•	Pastry Bake with Pizza mode	•	SmartZone	true
		Pyrolytic self-clean	•	Zone bridging	•
		Rapid proof	•	Zone Snaging	
Installation Dimensions		Roast	•		
Installation cutout dimensions (Depth)	600 mm	Rotisserie	•	Rangetop Performance	
Installation cutout dimensions (Width)	900 mm			Centre	2300 W
				Left front zone rating	1600 (1850) W
		Oven performance		Left rear zone rating	2100 (3000) W
Main oven features		CoolTouch door	Quadruple glazed	Number of cooking zones	5
Internal light	•	Grill power	4500W	PowerBoost	3000
		Warming drawer power	202 W	Right front zone rating	1600 (1850) W
				5	

QUICK REFERENCE GUIDE > OR90SPI6X1

Right rear zone rating 2100 (3000) W Safety Advanced cooling system Anti-tilt bracket Balanced oven door Catalytic venting system Child lock CoolTouch door Full extension telescopic sliding shelves Non-tip shelves Pan detection system Safety time out Spill containment 1.2 L Spillage auto off Surface hot indicators

Warranty

Parts and labour	2 years

SKU 82724

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

