

60cm Series 9 Integrated Triple Zone Refrigerator

Series 9 | Integrated

Panel Ready | Right Hinge



Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution – this model features three independent food zones taking cooling flexibility to a new level.

- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation
- Convenient access to fresh, chilled water with internal water dispenser

- Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

| | |
|--------|---------|
| Height | 1870 mm |
| Width | 592 mm |
| Depth | 576 mm |

FEATURES & BENEFITS

Three Levels Of Freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Slimline Water Dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories (included)

Hinge change (from right hinge to left hinge)

Accessories (sold separately)

Door panel set stainless steel

Right & Left hinge RD6019

| | |
|--|---------------|
| Handle kit Classic | AHCLRDSF |
| Handle kit Contemporary round, aluminium | AHSRDSF |
| Handle kit Contemporary square fine, aluminium | AHD5RDSF |
| Handle kit Contemporary square fine, black | AHD5RDSFB |
| Handle kit Professional round flush | AHP3RDSF |
| Joiner Kit | AJRS19LR |
| Toe kick stainless steel 1200mm | AKRS12010 |
| Toe kick stainless steel 1800mm | AKRS18010 |
| Toe kick stainless steel 600mm | AKRS06010 |
| Water filter replacement | 847200 - FWC3 |

| | |
|--------------------------|-----|
| LED ceiling lighting | • |
| LED side lighting | • |
| SmartTouch control panel | • |
| Stackable bottle holders | 2 |
| Water tank capacity | 1 L |

Installation Dimensions

| | |
|---|---------|
| Minimum inside width of cabinetry frame | 600 mm |
| Minimum internal depth of cabinetry | 600 mm |
| Minimum internal height of cabinetry | 1880 mm |

Performance

| | |
|----------------------------------|-----------------------|
| ActiveSmart™ Foodcare | • |
| Adaptive defrost | • |
| Frost free | • |
| Humidity control system | • |
| Humidity controlled crisper bins | 4 |
| Inverter controlled compressor | • |
| Sabbath mode | • |
| Triple evaporator | • |
| Variable food modes | Pantry; Fridge; Chill |
| Variable temperature zones | 3 |

Power requirements

| | |
|------------------|-------|
| Amperage | 10 A |
| Supply frequency | 50 Hz |
| Supply voltage | 230 V |

Product dimensions

| | |
|--------|---------|
| Depth | 576 mm |
| Height | 1870 mm |
| Width | 592 mm |

Warranty

| | |
|--------------------------|---------|
| Parts and labour | 2 years |
| Sealed system parts only | 5 years |

SKU 26207

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) 2D-DWG Integrated Refrigeration - K08 Hinge
- [↓](#) 2D-DWG Refrigerator
- [↓](#) 2D-DWG Refrigerator with Custom Panel
- [↓](#) 2D-DXF Integrated Refrigeration - K08 Hinge
- [↓](#) 2D-DXF Refrigerator
- [↓](#) 2D-DXF Refrigerator with Custom Panel
- [↓](#) 2D-DXF Integrated Refrigeration - Panel Preparation
- [↓](#) Archicad 23 Refrigerator
- [↓](#) Energy Label Integrated Triple Zone Refrigerator
- [↓](#) Service & Warranty

Capacity

| | |
|----------------------|-------|
| Total gross capacity | 330 L |
| Volume | 306 L |
| Volume refrigerator | 306 L |

Consumption

| | |
|---|-----------------|
| Energy consumption | 131kWh/year |
| Energy rating | 4 ticks |
| In-use energy carbon emissions estimate | 50.2kgCO2e/year |

Features

| | |
|---------------------------------------|---|
| Adjustable door shelves | 4 |
| Adjustable glass cantilevered shelves | • |
| Covered door shelves | 1 |
| Door alarm | • |
| Internal water dispenser | • |
| LED bin lighting | • |

- [↓ Installation Guide Integrated Refrigeration](#)
- [↓ Planning Guide Integrated Refrigeration](#)
- [↓ Revit 18 Refrigerator](#)
- [↓ Rhino 5 Refrigerator](#)
- [↓ Rhino 5 Refrigerator with Custom Panel](#)
- [↓ Rhino 5 Refrigerator Door with Classic Round Handle](#)
- [↓ Rhino 5 Refrigerator Door with Contemporary Round Handle](#)
- [↓ Rhino 5 Refrigerator Door with Professional Round Flush Handle](#)
- [↓ Rhino 5 Refrigerator Door with Square Fine Black Handle](#)
- [↓ Rhino 5 Refrigerator Door with Square Fine Handle](#)
- [↓ Sketchup 8 Refrigerator](#)
- [↓ Sketchup 8 Refrigerator with Custom Panel](#)
- [↓ Sketchup 8 Refrigerator Door with Classic Round Handle](#)
- [↓ Sketchup 8 Refrigerator Door with Contemporary Round Handle](#)
- [↓ Sketchup 8 Refrigerator Door with Professional Round Flush Handle](#)
- [↓ Sketchup 8 Refrigerator Door with Square Fine Black Handle](#)
- [↓ Sketchup 8 Refrigerator Door with Square Fine Handle](#)
- [↓ User Guide Integrated Refrigerator & Freezer](#)



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T +65 6741 0777 W www.fisherpaykel.com

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.