QUICK REFERENCE GUIDE > RS6019S2R1 Date: 30.10.2024 > 1

60cm Series 9 Integrated Dual Zone Refrigerator

Series 9 | Integrated

Panel Ready | Right Hinge



Pair with the Integrated Dual Zone Freezer for the ultimate kitchen solution – this model features two independent food zones taking cooling flexibility to a new level.

- Flush fit design with 4mm gaps and custom height installation
- Two independent food zones with adjustable temperature from 1 to 6°C
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory

Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm
Width 592 mm
Depth 576 mm

FEATURES & BENEFITS

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Independent Food Zones

When it comes to optimal food preservation, one temperature does not fit all. With two independent food zones, you can create the perfect climate for storing different foods. Each zone has adjustable temperature from 1°C to 6°C, ideal for items such as fruit and vegetables, dairy products, meats and leftoyers.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Flexible Storage

Designed to make it simple for you to store, access and remove food, this refrigerator includes LED-lit adjustable cantilevered shelving and full extension veggie bins.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories (included)

Hinge change (from right hinge to left hinge)

Accessories (sold separately)

Door panel set stainless steel Right & Left hinge RD6019

Handle kit Classic AHCLRDSF

Handle kit Contemporary round, aluminium

Handle kit Contemporary square fine, aluminium

AHD5RDSF

AHSRDSF

| andle kit Contemporary square fine, black AHD | 5RDSFB | |
|--|-----------|--|
| andle kit Professional round flush AF | 1P3RDSF | |
| iner Kit A | JRS19LR | |
| e kick stainless steel 1200mm Ak | (RS12010 | |
| e kick stainless steel 1800mm Ak | AKRS18010 | |
| e kick stainless steel 600mm AK | RS06010 | |
| pacity | | |
| tal gross capacity | 338 L | |
| olume | 314 L | |
| olume refrigerator | 314 L | |
| nsumption | | |
| nergy rating | E | |
| nergy usage 101k | Wh/yea | |
| -use energy carbon emissions estimate 31.2kgCo | O2e/yeaı | |
| atures | | |
| djustable door shelves | 4 | |
| djustable glass cantilevered shelves | • | |
| | 1 | |
| overed door shelves | | |
| overed door shelves oor alarm | • | |
| | • | |
| por alarm | • | |
| oor alarm ED ceiling lighting | • | |

| Minimum inside width of cabinetry frame | 600 mm |
|--|------------------------|
| Minimum internal depth of cabinetry | 600 mm |
| Minimum internal height of cabinetry | 1880 mm |
| Performance | |
| ActiveSmart™ Foodcare | • |
| Adaptive defrost | • |
| Dual evaporator | • |
| Frost free | • |
| Humidity control system | • |
| Humidity controlled crisper bins | 2 |
| Inverter controlled compressor | • |
| Sabbath mode | • |
| Amperage Supply frequency Supply voltage | 10 A 50 Hz 230 V |
| Product dimensions | |
| Depth | 576 mm |
| Height | 1870 mm |
| Width | 592 mm |
| Warranty | |
| Parts and labour | 5 years |
| Sealed system parts only | 5 years |
| | |

SKU 26206

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

| $\underline{\downarrow}$ | 2D-DWG Integrated Refrigeration - K08 Hinge |
|-------------------------------------|---|
| $\overline{\downarrow}$ | 2D-DWG Refrigerator |
| <u>→</u> | 2D-DWG Refrigerator with Custom Panel |
| $\underline{\downarrow}$ | 2D-DXF Integrated Refrigeration - K08 Hinge |
| $\underline{\downarrow}$ | 2D-DXF Refrigerator |
| $\underline{\downarrow}$ | 2D-DXF Refrigerator with Custom Panel |
| <u>↓</u> | 2D-DXF Integrated Refrigeration - Panel Preparation |
| $\underline{\downarrow}$ | Archicad 23 Refrigerator |
| $\underline{\downarrow}$ | Declaration of Conformity Refrigeration with WiFi Capability |
| $\underline{\downarrow}$ | Declaration of Conformity |
| $\underline{\downarrow}$ | Energy Rating |
| $\overline{\downarrow}$ | Service & Warranty |
| $\underline{\downarrow}$ | Installation Guide Integrated Refrigeration |
| | Planning Guide Integrated Refrigeration |
| <u>↓</u> | Product Information Sheet Integrated Dual Zone Refrigerator |
| $\overline{\underline{\downarrow}}$ | Revit 18 Refrigerator |
| $\underline{\downarrow}$ | Rhino 5 Refrigerator |
| $\overline{4}$ | Rhino 5 Refrigerator with Custom Panel |
| $\overline{\downarrow}$ | Rhino 5 Refrigerator Door with Classic Round Handle |
| $\underline{\downarrow}$ | Rhino 5 Refrigerator Door with Contemporary Round Handle |
| $\underline{\downarrow}$ | Rhino 5 Refrigerator Door with Professional Round Flush Handle |

Rhino 5 Refrigerator Door with Square Fine Black Handle Rhino 5 Refrigerator Door with Square Fine Handle **QUICK REFERENCE GUIDE >** RS6019S2R1 Date: 30.10.2024 > 3

- Sketchup 8 Refrigerator
- Sketchup 8 Refrigerator with Custom Panel
- ↓ Sketchup 8 Refrigerator Door with Classic Round Handle
- Sketchup 8 Refrigerator Door with Professional Round Black Handle
- ↓ Sketchup 8 Refrigerator Door with Square Fine Black Handle
- ↓ Sketchup 8 Refrigerator Door with Classic Fine Handle

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1800 625174 Wwww.fisherpaykel.com