

Integrated Column Refrigerator, 24"

Series 11 | Integrated


Panel Ready | Right Hinge



- <p>Install it separately or pair with another Column for seamless integration - this model is right hinge with stainless steel interior.</p>
- ActiveSmart™ technology helps keep food fresher for longer by constantly maintaining the ideal temperature
 - Two separate Variable Temperature Zones: each with Fridge, Pantry or Chill
 - Customize with your own kitchen cabinetry or purchase our stainless steel door panel accessory

DIMENSIONS

Height	84 "
Width	23 3/4 "
Depth	24 "



FEATURES & BENEFITS

- Variable Temperature Zones**
- Food is stored in two separate zones. You have the choice of three food modes: Fridge 32°F to 44°F, Pantry 52°F to 56°F and Chill 29°F to 32°F.
- Mix & Match**

- Integrated Column Refrigeration gives you the freedom to mix and match. Different sized Column Fridges and Freezers can be installed separately or paired. Finish them with our stainless steel door panels or customize to match your own kitchen cabinetry.
- Clever Energy**
- Our Energy Star certified ActiveSmart™ Foodcare Fridges & Freezers adapt to daily use by cooling and defrosting only when needed. This means your refrigerator uses the energy it needs without compromising on food care.
- Appealing Illumination**
- Bright LEDs light up the ceiling, shelves, bins and tray in both refrigerator and freezer, making it easy to find your food and creating a welcoming glow in your kitchen for those midnight snacks.
- Design Quality**
- The premium design and quality finish includes a steel interior lining as well as soft-close, full extension metal shelf runners for easy access and robust glass shelving.
- Easy Install**
- Integrated Column Refrigerators and Freezers have been developed to make their installation easy. The joiner kit is included when pairing refrigerator and freezers. All models come with front adjustable levelling feet and they've been designed to easily slide into place as separate units.
- Perfect Fit**
- These models fit flush and have only 1/8" gaps around them with no visible hinges or grilles. Our Integrated Column models can be seamlessly hidden behind your cabinetry or you can purchase our stainless steel door panel.
- SPECIFICATIONS**
- Accessories (sold separately)

Handle kit Contemporary round, aluminium	AHSRDSF	Features		Product Dimensions	
Handle kit Contemporary square fine, aluminium	AHD5RDSF	Adjustable door shelves	4	Depth	24 "
Handle kit Contemporary square fine, black	AHD5RDSFB	Adjustable glass cantilevered shelves	•	Height	84 "
Handle kit Professional round flush	AHP3RDSF	Covered door shelves	1	Width	23 3/4 "
Handle kit Professional round flush, Brass off-stands	AHP3RDSFBA	Door alarm	•		
Handle kit Professional round flush, Dark Copper off-stands	AHP3RDSFDC	Fruit and vegetable bins	4		
Joiner Kit	AJ-RS84LR	Gallon door shelves	1	Product information	
Stainless steel door panel	24" Right hinge RD2484R4D	LED bin lighting	•	Packaged weight	275 lbs
Toe kick stainless steel 24"	AKRS2404	LED ceiling lighting	•	Unpackaged weight	258 lbs
Toe kick stainless steel 42"	AKRS4204	LED lighting	•		
Toe kick stainless steel 48"	AKRS4804	LED side lighting	•	Safety and compliance	
Toe kick stainless steel 54"	AKRS5404	SmartTouch interface at counter height	•	ADA compliant	•
Toe kick stainless steel 60"	AKRS6004	Soft-close fruit and vegetable bins	•		
Toe kick stainless steel 66"	AKRS6604	Stackable bottle holders	4		
Toe kick stainless steel 72"	AKRS7204			Warranty	
Toe kick stainless steel 78"	AKRS7804	Performance		Parts and labor	2 years
Toe kick stainless steel 84"	AKRS8404	ActiveSmart™ Foodcare	•	Sealed system parts & labor	additional 3 years
		Dual evaporator	•		
		Frost free	•		
		Humidity control system	•	SKU	26121
		Inverter controlled compressor	•		
		Sabbath mode	•		
		Variable food modes	Pantry; Fridge; Chill		
		Variable temperature zones	2		
				The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020	
		Power Requirements		Other product downloads available at fisherpaykel.com	
		Rated current	10 A		
		Supply frequency	60 Hz		
		Supply voltage	115 V		

- [↓ 2D-DWG Integrated Column Refrigerator](#)
- [↓ 2D-DXF Integrated Column Refrigerator](#)
- [↓ Data Sheet Integrated Column Refrigerator](#)
- [↓ Data Sheet Integrated Column Refrigerator Dual Install \(18" + 24"\)](#)
- [↓ Data Sheet Integrated Column Refrigerator Dual Install \(24" + 24"\)](#)
- [↓ Data Sheet Integrated Column Refrigerator Dual Install \(24" + 30"\)](#)
- [↓ Energy Label](#)
- [↓ Service & Warranty](#)
- [↓ Installation Guide](#)
- [↓ Installation Guide Toe Kick](#)
- [↓ Guide d'installation - Instructions de Remplacement du Filtre à Eau FR](#)
- [↓ Installation Guide](#)
- [↓ Key Purchase Decisions Integrated Column Refrigerator](#)
- [↓ Planning Guide Professional Style Dial/Handle Accessories](#)
- [↓ Planning Guide Integrated Column Refrigerator](#)
- [↓ Revit Refrigerator](#)
- [↓ Rhino Refrigerator with Custom Panel](#)
- [↓ Rhino Refrigerator Door with Contemporary Round Handle](#)
- [↓ Rhino Refrigerator Door with Contemporary Square Handle](#)
- [↓ Rhino Refrigerator Door with Professional Round Handle](#)
- [↓ Rhino Refrigerator Door with Professional Square Handle](#)
- [↓ SketchUp Refrigerator with Custom Panel](#)
- [↓ SketchUp Refrigerator Door with Contemporary Round Handle](#)
- [↓ SketchUp Refrigerator Door with Contemporary Square Handle](#)
- [↓ SketchUp Refrigerator Door with Professional Round Handle](#)
- [↓ SketchUp Refrigerator Door with Professional Square Handle](#)
- [↓ Specification Guide Integrated Column Refrigerator](#)
- [↓ User Guide EN](#)
- [↓ User Guide](#)

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
 T 1.888.936.7872 W www.fisherpaykel.com

Where applicable: