
QUICK REFERENCE GUIDE > HC30PCX1

# Wall Range Hood, 30", Pyramid Chimney

Series 7 | Classic

Stainless Steel



Pairing well with the stainless steel Classic Range, this wall chimney range hood extracts steam, grease and cooking odors effectively.

- With three fan speeds, select the perfect extraction rate for your cooking
- Dishwasher-safe filters that are easy to remove and clean
- Powerful 600 CFM maximum airflow with edge-to-edge extraction
- · Energy-efficient LED lighting to illuminate your cooktop

#### **DIMENSIONS**

Height 38 3/8 - 21 1/16 "

Width 29 3/4 "

Depth 19 11/16 "

## **FEATURES & BENEFITS**

#### Complementary Design

This wall chimney range hood is designed to match the classic Range in both colour and style, including stylish chrome touch buttons.

#### Cleaner Air

Odors can linger in the kitchen well after cooking is finished. With three fan speeds and a maximum airflow of 600CFM, this range hood removes cooking odors effectively, as well as grease and steam while cooking.

## **Intuitive Controls**

Classic-style chrome touch buttons are simple to use, giving you full control of your extraction.

#### Simple To Clean

Three stainless steel filters are easy to remove, and can be cleaned in the dishwasher or washed by hand in hot soapy water.

## **Design Quality**

Made from quality stainless steel with an excellent finish and robust product design, this range hood is both visually appealing and durable.

#### Considered Efficiency

The extraction rate ensures interior air is not excessively removed to the outside, while LED lighting on the range hood has been chosen for energy efficiency.

#### Easy Installation

This wall chimney rangehood is the perfect partner to your Fisher & Paykel Cooktop or Range. It can be either externally ducted or internally recirculated, for simple installation.

## **SPECIFICATIONS**

Accessories (included)	
Aluminium filter	792558
Accessories (sold separately)	
Chimney extension	791774
Light bulb	792579
Recirculation carbon filter	793162
Recirculation diverter	793163
Fan ratings	
Maximum air movement	600 CFM
Installation and cleaning	
Air outlet size	8" "
Ducted	Vertical only
Recirculation	Optional
Stainless steel filter cover	•
Two piece height adjustable flue	•

QUICK REFERENCE GUIDE > HC30PCX1

Performa	ance
----------	------

Extraction type	Surface
Fan speeds	3
Filter type	Mesh
Number of filters	2

#### Power requirements

Lighting power	8 W
Supply frequency	60 Hz
Supply voltage	120 V

## **Product dimensions**

Depth	19 11/16 "
Height	38 3/8 - 21 1/16 "
Width	29 3/4 "

# **Product information**

Control type	Classic style
	chrome touch
	buttons

## Ventilation features

Light type	LEC	
------------	-----	--

SKU	50156

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

## Other product downloads available at fisherpaykel.com

Guide d'installation et guide d'utilisation FR

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

